

Compressed Air Hose



Steel Wire Air Hose



Applications

- High pressure air hose for heavy-duty use in mines, quarries, construction and industry.

Cover

- Yellow, SBR rubber, offering excellent abrasion and weather resistance - pin pricked.

Reinforcement

- High tensile spiral steel wire.

Tube

- Black SBR/NBR - resistant to oil mist.

Branding

- Embossed - ALFAGOMMA - ITALY - T130 STEEL AIR

Item #	Nominal I.D.	Nominal O.D.	Max. Rec. Working Pressure	Min. Bend Radius	Temperature Range
T130AK050	1/2 in 13 mm	0.98 in 25 mm	600 psi	2 1/2 in	-22 to 176 °F
T130AK075	3/4 in 19.0 mm	1.22 in 31 mm	600 psi	4 in	-22 to 176 °F
T130AK100	1 in 25 mm	1.46 in 37 mm	600 psi	5 in	-22 to 176 °F
T130AK125	1 1/4 in 32 mm	1.73 in 44 mm	600 psi	6 in	-22 to 176 °F
T130AK150	1 1/2 in 38 mm	2.05 in 52 mm	600 psi	7 1/2 in	-22 to 176 °F
T130AK200	2 in 51 mm	2.56 in 65 mm	600 psi	10 in	-22 to 176 °F
T130AK250	2 1/2 in 63 mm	3.27 in 83 mm	450 psi	12 in	-22 to 176 °F
T130AK300	3 in 76 mm	3.78 in 96 mm	450 psi	15 in	-22 to 176 °F
T130AK400	4 in 102 mm	4.80 in 122.0 mm	450 psi	20 in	-22 to 176 °F

High Temperature Steel Wire Reinforced Air Hose



Applications

- High pressure air for mines and quarries. Designed for long lasting service and maximum safety in heavy duty applications where resistance to high temperature is required.

Cover

- Yellow EPDM - abrasion and ozone resistant - pin pricked.

Reinforcement

- High tensile steel cords.

Tube

- Black Chlorobutyl.

Branding

- ALFAGOMMA - ITALY T133 HI TEMP STEEL AIR - Embossed..

Item #	Nominal I.D.	Nominal O.D.	Max. Rec. Working Pressure	Min. Bend Radius	Construction	Temperature Range
T133AK200	2 in 51 mm	2.56 in 65 mm	600 psi	10 in	Braided	-31 to 338 °F
T133AK250	2 1/2 in 63 mm	3.26 in 83 mm	600 psi	12 in	Spiral	-31 to 338 °F
T133AK300	3 in 76 mm	3.70 in 94 mm	600 psi	15 in	Spiral	-31 to 338 °F

Textile Cord "Air Drill" Hose**Application**

- High quality air hose for mining and construction service.

Cover

- Yellow, abrasion and weather-resistant SBR rubber.

Reinforcement

- Spiraled, high tensile textile cords.

Tube

- Black SBR/NBR blend - oil mist resistant.

Branding

- ALFAGOMMA - ITALY - T155 20 BAR (300 PSI) AIR (in blue letters)

Item #	Nominal I.D.	Nominal O.D.	Max. Rec. Working Pressure	Temperature Range
T155AK050	1/2 in 13 mm	0.83 in 21 mm	300 psi	-22 to 176 °F
T155AK075	3/4 in 19.0 mm	1.14 in 29 mm	300 psi	-22 to 176 °F
T155AK100	1 in 25 mm	1.38 in 35 mm	300 psi	-22 to 176 °F
T155AK125	1 1/4 in 32 mm	1.73 in 44 mm	300 psi	-22 to 176 °F
T155AK150	1 1/2 in 38 mm	1.97 in 50 mm	300 psi	-22 to 176 °F
T155AK200	2 in 51 mm	2.56 in 65 mm	300 psi	-22 to 176 °F
T155AK250	2 1/2 in 63 mm	3.11 in 79 mm	300 psi	-22 to 176 °F
T155AK300	3 in 76 mm	3.62 in 92 mm	300 psi	-22 to 176 °F
T155AK400	4 in 102 mm	4.65 in 118 mm	300 psi	-22 to 176 °F

Textile Cord "Heavy Duty" Air Drill Hose**Application**

- High quality air hose for heavy duty and mining applications.

Cover

- Green, abrasion and weather-resistant SBR rubber.

Reinforcement

- Spiraled high tensile textile cords and 4 highly flexible steel helix wires.

Tube

- Black heat-resistant EPDM rubber.

Branding

- ALFAGOMMA - ITALY - T157 27 BAR (400 PSI) AIR (in blue letters)

Item #	Nominal I.D.	Nominal O.D.	Max. Rec. Working Pressure	Temperature Range
T157AG050	1/2 in 13 mm	0.91 in 23 mm	400 psi	-22 to 176 °F
T157AG075	3/4 in 19.0 mm	1.14 in 29 mm	400 psi	-22 to 176 °F
T157AG100	1 in 25 mm	1.38 in 35 mm	400 psi	-22 to 176 °F
T157AG125	1 1/4 in 32 mm	1.73 in 44 mm	400 psi	-22 to 176 °F
T157AG150	1 1/2 in 38 mm	1.97 in 50 mm	400 psi	-22 to 176 °F
T157AG200	2 in 51 mm	2.56 in 65 mm	400 psi	-22 to 176 °F