

# Creamery Washdown Hose



### Premium White Cover Paper Mill Creamery Wash Down Hose - No Nozzle



#### Application

- For general wash down service, using hot water or low pressure saturated steam in processing plants.

#### Cover

- White, heat and abrasion-resistant EPDM rubber.

#### Reinforcement

- High tensile textile cords.

#### Tube

- White EPDM rubber.

#### Branding

- ALFAGOMMA - ITALY - T350 7 BAR (100 PSI) STEAM 15 BAR (225 PSI) HOT WATER (embossed)

Item #	Nominal I.D.	Nominal O.D.	Working Pressure	Temperature Range
T350LL050	1/2 in 13 mm	0.91 in 23 mm	225 psi 15 bar	-40 to 330 °F
T350LL075	3/4 in 19.0 mm	1.22 in 31 mm	225 psi 15 bar	-40 to 330 °F
T350LL100	1 in 25 mm	1.46 in 37 mm	225 psi 15 bar	-40 to 330 °F

### Premium Paper Mill Creamery Wash Down Hose with Tapered Nozzle



#### Application

- For general wash down service, using hot water or low pressure saturated steam in processing plants.

#### Cover

- White or green, heat and abrasion-resistant EPDM rubber.

#### Reinforcement

- High tensile textile cords.

#### Tube

- White EPDM rubber.

Item #	Nominal I.D.	Nominal O.D.	Working Pressure	Temperature Range
T351LL075	3/4 in 19.0 mm	1.22 in 31 mm	150 psi 10 bar	-40 to 248 °F
T351LL100	1 in 25 mm	1.46 in 37 mm	150 psi 10 bar	-40 to 248 °F
T351LL125	1 1/4 in 32 mm	1.81 in 46 mm	150 psi 10 bar	-40 to 248 °F
T351LL150	1 1/2 in 38 mm	2.05 in 52 mm	150 psi 10 bar	-40 to 248 °F
T351LG075	3/4 in 19.0 mm	1.22 in 31 mm	150 psi 10 bar	-40 to 248 °F
T351LG100	1 in 25 mm	1.46 in 37 mm	150 psi 10 bar	-40 to 248 °F
T351LG125	1 1/4 in 32 mm	1.81 in 46 mm	150 psi 10 bar	-40 to 248 °F
T351LG150	1 1/2 in 38 mm	2.05 in 52 mm	150 psi 10 bar	-40 to 248 °F