

Petroleum Hose



Biofuel Petroleum Suction & Discharge Hose



For suction and discharge applications in truck and tank car transfer of gasoline, oil and Biofuels - up to E98 and B100 (T629 is not recommended for use on a reel.) with up to 60% aromatic content at ambient temperature.

| Item # | Nominal I.D. | Nominal O.D. | Min. Bend Radius | Approx. Weight per Feet | Working Pressure | Temperature Range |
|---------------|-------------------|--------------------|------------------|-------------------------|------------------|-------------------------------|
| T629AA075X100 | 3/4 in 19.0 mm | 1.14 in 29 mm | 3 in | .41 lb. | 150 psi | -22 to 176 °F -30 to 80 °C |
| T629AA100X100 | 1 in 25 mm | 1.38 in 35 mm | 4 in | .51 lb. | 150 psi | -22 to 176 °F -30 to 80 °C |
| T629AA125X100 | 1 1/4 in 32 mm | 1.65 in 42 mm | 5 in | .60 lb. | 150 psi | -22 to 176 °F -30 to 80 °C |
| T629AA150X100 | 1 1/2 in 38 mm | 1.89 in 48 mm | 6 in | .70 lb. | 150 psi | -22 to 176 °F -30 to 80 °C |
| T629AA200X100 | 2 in 51 mm | 2.40 in 61.0 mm | 8 in | .91 lb. | 150 psi | -22 to 176 °F -30 to 80 °C |
| T629AA250X100 | 2 1/2 in 63 mm | 2.95 in 75 mm | 10 in | 1.42 lb. | 150 psi | -22 to 176 °F -30 to 80 °C |
| T629AA300X100 | 3 in 76 mm | 3.46 in 88 mm | 12 in | 1.69 lb. | 150 psi | -22 to 176 °F -30 to 80 °C |
| T629AA400X100 | 4 in 102 mm | 4.57 in 116 mm | 16 in | 2.34 lb. | 150 psi | -22 to 176 °F -30 to 80 °C |

T650AH 150 PSI Oil Discharge Hose



Application: Oil discharge hose designed for use on trucks, docks or barges where a soft wall hose is required. Cover: Red CR - abrasion, ozone and hydrocarbon resistant. Reinforcement: Spiralled high tensile textile cords with embedded grounding wire. Grounding Wire: Physically extract the ground wire from the hose and bond to the metal coupling, or by other means, to ground. Tube: Black nitrile rubber for 50% aromatics. Temperature Range: -22°F (-30°C) to 176°F (+80°C) Branding: ALFAGOMMA - ITALY T650 10 BAR (150 PSI) - PETROLEUM DELIVERY (in yellow letters). Coupling Suggestions: Cam and groove or combination nipples attached with bands.

| Item # | Series | Branding | Nominal I.D. | Nominal O.D. | Working Pressure at 68°F | Length | Approx. Weight per Feet | Temperature Range |
|---------------|--------|------------|---------------------|---------------------|--------------------------|--------|-------------------------|-------------------------------|
| T650AH150X100 | T650AH | Alfagomma® | 1 1/2 in 38.1 mm | 1.89 in 48 mm | 150 psi | 100 ft | 0.62 lb. | -22 to 176 °F -30 to 80 °C |
| T650AH200X100 | T650AH | Alfagomma® | 2 in 50.8 mm | 2.40 in 61.0 mm | 150 psi | 100 ft | 0.81 lb. | -22 to 176 °F -30 to 80 °C |
| T650AH300X100 | T650AH | Alfagomma® | 3 in 50.8 mm | 3.46 in 88 mm | 150 psi | 100 ft | 1.42 lb. | -22 to 176 °F -30 to 80 °C |
| T650AH400X100 | T650AH | Alfagomma® | 4 in 101.6 mm | 4.49 in 114.0 mm | 150 psi | 100 ft | 1.92 lb. | -22 to 176 °F -30 to 80 °C |

T620AA - 300 PSI Black Fuel & Oil Suction & Delivery Hose



Application: Fuel and oil suction and discharge for up to 50% aromatic content. Designed for heavy duty applications. Note: Not recommended for use on a reel. Cover: Black conductive CR – abrasion, ozone and hydrocarbon resistant. Reinforcement: High tensile textile cords, steel helix wires and static wire. Tube: Black conductive NBR. Temperature Range: -22°F (-30°C) to 176°F (+80°C) Branding: ALFAGOMMA - ITALY T620 - 20 BAR (300 PSI) PETROLEUM - S & D (in red letters) O. Coupling Suggestions: Quick-Acting, combination nipples attached with bands or internally expanded brass couplings with gasket seal attached with ferrules.

| Item # | Series | Branding | Nominal I.D. | Nominal O.D. | Working Pressure | Min. Bend Radius | Temperature Range | Approx. Weight per Feet | Length |
|---------------|--------|------------|----------------|---------------------|------------------|------------------|-----------------------------|-------------------------|--------|
| T620AA200x100 | T620AA | Alfagomma® | 2 in 51 mm | 2.480 in 63 mm | 300 psi | 8 in | -22 to 176°F -30 to 80°C | 1.12 lb. | 100 ft |
| T620AA300x100 | T620AA | Alfagomma® | 3 in 76 mm | 3.540 in 90 mm | 300 psi | 12 in | -22 to 176°F -30 to 80°C | 1.78 lb. | 100 ft |
| T620AA400x100 | T620AA | Alfagomma® | 4 in 102 mm | 4.570 in 116 mm | 300 psi | 16 in | -22 to 176°F -30 to 80°C | 2.41 lb. | 100 ft |
| T620AA600x100 | T620AA | Alfagomma® | 6 in 152 mm | 6.69 in 170.0 mm | 300 psi | 24 in | -22 to 176°F -30 to 80°C | 5.16 lb. | 100 ft |

Bottom Loading Hose



Bottom Loading hose is engineered specifically for bottom loading, high pressure tank truck service. Construction of this hose has been stabilized to prevent elongation during service. This hose is rated at full vacuum. The black neoprene cover has excellent resistance to abrasion, weathering and ozone. The NBR tube is resistant to oil. Bottom Loading hose has a reinforcement of tire cord with a dual wire helix that allows this to handle a constant working pressure of 250 psi for both the 3" or 4" I.D.

Cover Color :Black

- Oil Resistance :High
- Construction :
- Tube :NBR with an aromatic range up to 55%
- Cover :CR
- Reinforcement :Tire cord with dual wire helix (es)
- Temperature Range :-20°F to +200°F (-29°C to +93°C)

| Item # | I.D. | O.D. | Plies | Working Pressure | Min. Bend Radius | Temperature Range |
|-------------|------------------|----------------------|-------|---------------------|--------------------|-----------------------------|
| 17811503002 | 3 in 76.2 mm | 3 3/4 in 95.25 mm | 4 | 250 psi 1.72 MPa | 12 in 304.80 mm | -20 to 200°F -29 to 93°C |
| 17811504002 | 4 in 101.6 mm | 4.88 in 123.83 mm | 4 | 250 psi 1.72 MPa | 18 in 457.20 mm | -20 to 200°F -29 to 93°C |

Cobra™ Fuel Oil Delivery Hose

Cobra Fuel Oil Delivery hose is designed for the delivery and transfer of fuels, oils, commercial gasoline, diesel, kerosene and related petroleum-based products for home delivery, marine, commercial and industrial service. It features an NBR/PVC cover with multiple spiral polyester reinforcement. This unique spiral construction adds strength and flexibility to the hose while making it easy to handle and kink resistant. The smooth, durable cover resists oil and abrasion and is less resistant to dragging, making it the driver's choice. This hose provides top performance and offers a constant working pressure of 250 psi in all sizes.

- **Note :** A static wire is included on all sizes as a safety precaution.

- **Cover Color :** Red
- **Oil Resistance :** High
- **Construction :**
 - Tube :** NBR, RMA Class
 - Cover :** NBR/PVC, RMA Class A
 - Reinforcement :** High tensile spiral polyester cord
- **Temperature Range :** -40°F to +180°F (-40°C to +82°C)
- **Packaging :** Reels

| Item # | Nominal I.D. | Nominal O.D. | Plies | Working Pressure | Min. Bend Radius | Temperature Range |
|-------------|----------------------|---------------------|-------|---------------------|----------------------|-------------------------------|
| 22564642662 | 1 in 25.4 mm | 1 1/2 in 38.1 mm | 4 | 250 psi 1.72 MPa | 7 in 177.80 mm | -40 to 180 °F -40 to 82 °C |
| 22564802662 | 1 1/4 in 31.75 mm | 1.78 in 45.24 mm | 4 | 250 psi 1.72 MPa | 8.75 in 222.25 mm | -40 to 180 °F -40 to 82 °C |
| 22564882662 | 1 3/8 in 34.93 mm | 1.88 in 47.63 mm | 4 | 250 psi 1.72 MPa | 9.25 in 234.95 mm | -40 to 180 °F -40 to 82 °C |
| 22564962662 | 1 1/2 in 38.1 mm | 2.09 in 53.18 mm | 4 | 250 psi 1.72 MPa | 10.5 in 266.70 mm | -40 to 180 °F -40 to 82 °C |

Pumpflex® I - Softwall Hose

Pumpflex I is designed for curb pump self-service stations and highly sensitive electronic fuel pumps. Pumpflex I is the longest lasting automotive refueling hose in use at service stations today. The durable construction of this hose resists deterioration from fuel in the tube. The cover stands up to the ravages of ozone and sunlight. Many hoses fail from cracking behind the nozzle end coupling within two to three years, but Pumpflex I will last longer under normal circumstances. Thermoid continues to use industry standard permanent chrome-plated brass couplings, while others do not. When you need a hose, use the best : Pumpflex I.

- **Note :** Do not use reusable couplings with this product.
- **Cover Color :** Black
- **Oil Resistance :** High, Medium-High
- **Construction :**
 - Tube :** NBR/PVC, RMA Class A
 - Cover :** Thermalon® 8482, U/L approved, Class B
 - Reinforcement :** Spiral polyester cord with static wire (Softwall)
- **Temperature Range :** -40°F to +180°F (-40°C to +82°C)
- **Packaging :** Reels

| Item # | Nominal I.D. | Nominal O.D. | Plies | Working Pressure | Min. Bend Radius | Temperature Range |
|-------------|--------------------|----------------------|-------|---------------------|---------------------|-------------------------------|
| 22462401662 | 5/8 in 15.88 mm | 1.030 in 26.19 mm | 2 | 200 psi 1.38 MPa | 3.75 in 95.25 mm | -40 to 180 °F -40 to 82 °C |
| 22462481662 | 3/4 in 19.05 mm | 1.13 in 28.58 mm | 2 | 200 psi 1.38 MPa | 4.5 in 114.30 mm | -40 to 180 °F -40 to 82 °C |
| 22464641662 | 1 in 25.4 mm | 1 1/2 in 38.1 mm | 2 | 150 psi 1.03 MPa | 7 in 177.80 mm | -40 to 180 °F -40 to 82 °C |

Pumpflex® II - Jumper Hose

Pumpflex II - Jumper hose primary application is the dual low hose dispenser converted to Stage II vapor recovery external liquid line connection. This hose is used in conjunction with the Pumpflex II hose.

- **Note : Do not use reusable couplings with this product.**
- **Cover Color :** Black
- **Oil Resistance :** High, Medium-High
- **Construction :**

Tube : NBR/PVC, RMA Class A
Cover : Thermalon™, U/L approved, Class A
Reinforcement : 1 wire braid (Hardwall)

- **Temperature Range :** -40°F to +180°F (-40°C to +82°C)
- **Packaging :** Bulk

| Item # | Series | Nominal I.D. | Weight | Temperature Range |
|-------------|----------|--------------------|-------------------------|-------------------------------|
| 22341481271 | 22341481 | 3/4 in 19.05 mm | 1.21 lb/ft 1.78 kg/m | -40 to 180 °F -40 to 82 °C |
| 22341481051 | 22341481 | 3/4 in 19.05 mm | 1.11 lb/ft 1.63 kg/m | -40 to 180 °F -40 to 82 °C |
| 22341481561 | 22341481 | 3/4 in 19.05 mm | 1.04 lb/ft 1.54 kg/m | -40 to 180 °F -40 to 82 °C |
| 22341481061 | 22341481 | 3/4 in 19.05 mm | 0.93 lb/ft 1.40 kg/m | -40 to 180 °F -40 to 82 °C |
| 22341481571 | 22341481 | 3/4 in 19.05 mm | 0.86 lb/ft 1.28 kg/m | -40 to 180 °F -40 to 82 °C |

Pumpflex® Marina - Softwall Hose

Pumpflex Marina hose is color coded green for marina use. This durable hose is designed to handle severe weather conditions, rough deck or dock use. It has a durable four spiral construction and static wire for continuity. This hose can be used for all types of gasoline, oil and other petroleum products. The green cover is oil and weather resistant as well as being UL approved.

- **Cover Color :** Green
- **Oil Resistance :** High, Medium-High

- **Construction :**
Tube : NBR/PVC, RMA Class A
Cover : CM, RMA Class B
Reinforcement : Spiral polyester yarn
- **Temperature Range :** -40°F to +180°F (-40°C to +82°C)
- **Packaging :** Reels

| Item # | Nominal I.D. | Nominal O.D. | Reinforcement Spirals | Working Pressure | Min. Bend Radius | Temperature Range |
|-------------|--------------------|----------------------|-----------------------|---------------------|---------------------|-------------------------------|
| 22463404662 | 5/8 in 15.88 mm | 1.030 in 26.19 mm | 4 | 200 psi 1.38 MPa | 3.75 in 95.25 mm | -40 to 180 °F -40 to 82 °C |
| 22463484662 | 3/4 in 19.05 mm | 1.13 in 28.58 mm | 4 | 200 psi 1.38 MPa | 4.5 in 114.30 mm | -40 to 180 °F -40 to 82 °C |
| 22464644662 | 1 in 25.4 mm | 1 1/2 in 38.1 mm | 4 | 150 psi 1.03 MPa | 7 in 177.80 mm | -40 to 180 °F -40 to 82 °C |

Hi-Vac™ Whip Hose

Hi-Vac Whip hose's primary application is the "breakaway" connection from the pump to the primary hose assembly. This hose is used in conjunction with the Hi-Vac™ Co-Ax® hose assembly.

- **Note : Do not use reusable couplings with this product.**
- **Coupling :** Chrome plated brass metric thread (M34).
- **Cover Color :** Black

- **Construction :**
Inner Hose Tube : NBR/PVC
Outer Hose Tube : NBR/PVC, RMA Class A
Inner Hose Cover : NBR/PVC
Outer Hose Cover : CSM, RMA Class B
Reinforcement : Braided steel wire
- **Temperature Range :** -40°F to +180°F (-40°C to +82°C)

| Item # | Series | Nominal I.D. | Temperature Range |
|-------------|--------|--------------------|-------------------------------|
| 22471111031 | 2247 | 3/4 in 19.05 mm | -40 to 180 °F -40 to 82 °C |
| 22471111011 | 2247 | 3/4 in 19.05 mm | -40 to 180 °F -40 to 82 °C |
| 22473222021 | 2247 | 7/8 in 22.23 mm | -40 to 180 °F -40 to 82 °C |
| 22473222011 | 2247 | 7/8 in 22.23 mm | -40 to 180 °F -40 to 82 °C |

Transporter® Ebonite™ Corrugated Tank Truck Hose

The Transporter Ebonite Corrugated Tank Truck hose is recommended for hydrocarbons with aromatic content up to 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals. This hose features a flat corrugated NBR/PVC cover which is ideal for those applications where flexibility is an issue. The reinforcement of two plies of polyester cord with a dual wire helix enables this hose to be rated at full vacuum. Also, this construction allows each size to have a constant working pressure of 150 psi.

- **Cover Color :** Black
- **Oil Resistance :** High
- **Construction :**

Tube : NBR, RMA Class A

Cover : NBR/PVC corrugated, RMA Class B

Reinforcement : 2 plies of polyester cord with a dual wire helix (es) between plies

- **Temperature Range :** -30°F to +200°F (-34°C to +93°C)

| Item # | Nominal I.D. | Nominal O.D. | Plies | Working Pressure | Min. Bend Radius | Temperature Range |
|-------------|----------------------|----------------------|-------|---------------------|---------------------|-------------------------------|
| 17813045002 | 1 in 25.4 mm | 1.53 in 38.89 mm | 2 | 150 psi 1.03 MPa | 2 in 50.80 mm | -30 to 200 °F -34 to 93 °C |
| 17813046002 | 1 1/4 in 31.75 mm | 1.78 in 45.24 mm | 2 | 150 psi 1.03 MPa | 2.5 in 63.50 mm | -30 to 200 °F -34 to 93 °C |
| 17813047002 | 1 1/2 in 38.1 mm | 2.06 in 52.39 mm | 2 | 150 psi 1.03 MPa | 3 in 76.20 mm | -30 to 200 °F -34 to 93 °C |
| 17813048002 | 2 in 50.8 mm | 2.56 in 65.09 mm | 2 | 150 psi 1.03 MPa | 4.5 in 114.30 mm | -30 to 200 °F -34 to 93 °C |
| 17813050002 | 3 in 76.2 mm | 3.56 in 90.49 mm | 2 | 150 psi 1.03 MPa | 6 in 152.40 mm | -30 to 200 °F -34 to 93 °C |
| 17813055002 | 4 in 101.6 mm | 4.66 in 118.27 mm | 2 | 150 psi 1.03 MPa | 8 in 203.20 mm | -30 to 200 °F -34 to 93 °C |

Transporter® Ebonite LT™ Corrugated Tank Truck Hose



The Transporter Ebonite LT Corrugated Tank Truck hose is designed to handle the applications for suction and discharge for tank truck, tank car and bulk station. This hose is used to convey gasoline, distilled kerosene, diesel and other fuels with maximum aromatic content of 30% to -65°F. This hose features a flat corrugated NBR cover which is ideal for those applications where flexibility and weight are issues. The two plies of polyester cord with a dual wire helix reinforcement allows this hose to be rated at full vacuum.

- **Cover Color :** Black
- **Oil Resistance :** Medium-High
- **Construction :**
 Tube : NBR (low temperature)
 Cover : NBR/PVC corrugated
 Reinforcement : 2 plies of polyester cord with a dual wire helix (es) between plies
- **Temperature Range :** -65°F to +180°F (-54°C to +82°C)

| Item # | Nominal I.D. | Nominal O.D. | Plies | Working Pressure | Min. Bend Radius | Temperature Range |
|-------------|---------------------|----------------------|-------|---------------------|---------------------|-------------------------------|
| 17813057002 | 1 1/2 in 38.1 mm | 2.06 in 52.39 mm | 2 | 150 psi 1.03 MPa | 3 in 76.20 mm | -65 to 180 °F -54 to 82 °C |
| 17813058002 | 2 in 50.8 mm | 2.56 in 65.09 mm | 2 | 150 psi 1.03 MPa | 4 in 101.60 mm | -65 to 180 °F -54 to 82 °C |
| 17813060002 | 3 in 76.2 mm | 3.56 in 90.49 mm | 2 | 150 psi 1.03 MPa | 5.5 in 139.70 mm | -65 to 180 °F -54 to 82 °C |
| 17813065002 | 4 in 101.6 mm | 4.66 in 118.27 mm | 2 | 150 psi 1.03 MPa | 8 in 203.20 mm | -65 to 180 °F -54 to 82 °C |

Transporter® Red Tank Truck Hose



The Transporter Red Tank Truck hose is recommended for use to handle the bulk transfer of petroleum products. This hose will also handle most hydrocarbons with aromatic content up to 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals. The NBR tube gives excellent resistance to oil. While the NBR/PVC cover is both oil and weather resistant. Transporter Red Tank Truck hose is rated at full vacuum.

- **Cover Color :** Red
- **Oil Resistance :** High
- **Construction :**

Tube : NBR, RMA Class A
Cover : NBR/PVC, RMA Class B
Reinforcement : Spiral steel wire helix (es) between synthetic textile plies

- **Temperature Range :** -30°F to +200°F (-34°C to +93°C)

| Item # | Nominal I.D. | Nominal O.D. | Plies | Working Pressure | Min. Bend Radius | Temperature Range |
|-------------|---------------------|----------------------|-------|---------------------|---------------------|-------------------------------|
| 17813015002 | 1 1/2 in 38.1 mm | 2 in 50.8 mm | 2 | 150 psi 1.03 MPa | 4.5 in 114.30 mm | -30 to 200 °F -34 to 93 °C |
| 17813020002 | 2 in 50.8 mm | 2.47 in 62.71 mm | 2 | 150 psi 1.03 MPa | 6 in 152.40 mm | -30 to 200 °F -34 to 93 °C |
| 17813025002 | 2 1/2 in 63.5 mm | 3.06 in 77.79 mm | 2 | 150 psi 1.03 MPa | 7.5 in 190.50 mm | -30 to 200 °F -34 to 93 °C |
| 17813030002 | 3 in 76.2 mm | 3.56 in 90.49 mm | 2 | 150 psi 1.03 MPa | 9 in 228.60 mm | -30 to 200 °F -34 to 93 °C |
| 17813040002 | 4 in 101.6 mm | 4.63 in 117.48 mm | 2 | 150 psi 1.03 MPa | 12 in 304.80 mm | -30 to 200 °F -34 to 93 °C |

Transporter® Black Tank Truck Hose

The Transporter Black Tank Truck hose is rated at full vacuum. Like the red version, this hose is recommended for most hydrocarbons with aromatic content up to 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals. The black NBR tube has high oil resistance. The NBR/PVC cover is both oil and abrasion resistant.

- **Cover Color :** Black
- **Oil Resistance :** High
- **Construction :**
Tube : NBR, RMA Class A
Cover : NBR/PVC, RMA Class B

Reinforcement : Spiral steel wire helix (es) between synthetic textile plies

- **Temperature Range :** -30°F to +200°F (-34°C to +93°C)

| Item # | Nominal I.D. | Nominal O.D. | Plies | Working Pressure | Min. Bend Radius | Temperature Range |
|-------------|----------------------|----------------------|-------|---------------------|---------------------|-----------------------------|
| 17811008002 | 1 in 25.4 mm | 1 1/2 in 38.1 mm | 2 | 200 psi 1.38 MPa | 2.5 in 63.50 mm | -30 to 200°F -34 to 93°C |
| 17811010002 | 1 1/4 in 31.75 mm | 1 3/4 in 44.45 mm | 2 | 200 psi 1.38 MPa | 3 in 76.20 mm | -30 to 200°F -34 to 93°C |
| 17811015002 | 1 1/2 in 38.1 mm | 2 in 50.8 mm | 2 | 150 psi 1.03 MPa | 4.5 in 114.30 mm | -30 to 200°F -34 to 93°C |
| 17811020002 | 2 in 50.8 mm | 2.47 in 62.71 mm | 2 | 150 psi 1.03 MPa | 6 in 152.40 mm | -30 to 200°F -34 to 93°C |
| 17811025002 | 2 1/2 in 63.5 mm | 3.06 in 77.79 mm | 2 | 150 psi 1.03 MPa | 7.5 in 190.50 mm | -30 to 200°F -34 to 93°C |
| 17811030002 | 3 in 76.2 mm | 3.56 in 90.49 mm | 2 | 150 psi 1.03 MPa | 9 in 228.60 mm | -30 to 200°F -34 to 93°C |
| 17811040002 | 4 in 101.6 mm | 4.63 in 117.48 mm | 2 | 150 psi 1.03 MPa | 12 in 304.80 mm | -30 to 200°F -34 to 93°C |
| 17811060002 | 6 in 152.4 mm | 6.78 in 172.24 mm | 2 | 100 psi 0.69 MPa | 30 in 762.00 mm | -30 to 200°F -34 to 93°C |

Transporter® Flex-Devil™ Hose

Flex-Devil is a transfer hose for gasoline, a wide range of oils and chemicals and petroleum based products. Flex-devil is made from special rubber compounds that produce an exceptional lightweight and

flexible hose for use in temperatures down to -40 deg F. Rated at FULL VACUUM, Flex-Devil is compatible with gasoline grades up to 50% aromatic content and MTBE/unleaded blends up to 15% MTBE. This hose accepts a range of coupling types: swaged, crimped, internally expanded or banded shank.

| Item # | Length | Nominal I.D. | Nominal O.D. | Working Pressure | Min. Bend Radius |
|-------------|--------|--------------|--------------|------------------|------------------|
| 17814532002 | 100 ft | 2 in | 2.43 in | 150 psi | 4.0 in |
| 17814534002 | 100 ft | 3 in | 3.47 in | 150 psi | 6.0 in |
| 17814536002 | 100 ft | 4 in | 4.54 in | 150 psi | 2.24 in |

Type 924 Petroleum Transfer Hose

Type 924 Petroleum Transfer hose is perfect for those applications for the bulk transfer of petroleum products. This hose can also be used to handle most hydrocarbons with aromatic content of 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals. The black NBR tube has excellent resistance to oil. The cover

compound of NBR/PVC is both oil and abrasion resistant. This hose is rated at FULL VACUUM!

| Item # | Nominal I.D. | Nominal O.D. | Working Pressure | Min. Bend Radius |
|-------------|--------------|--------------|------------------|------------------|
| 17812008002 | 1 in | 1 1/2 in | 200 psi | 2.5 in |
| 17812010002 | 1 1/4 in | 1 3/4 in | 200 psi | 3.0 in |
| 17812015002 | 1 1/2 in | 2 in | 150 psi | 4.5 in |
| 17812020002 | 2 in | 2 15/32 in | 150 psi | 6.0 in |
| 17812025002 | 2 1/2 in | 3 1/16 in | 150 psi | 7.5 in |
| 17812030002 | 3 in | 3 9/16 in | 150 psi | 9.0 in |
| 17812040002 | 4 in | 4 5/8 in | 150 psi | 12.0 in |
| 17774456002 | 6 in | 6 3/4 in | 100 psi | 30.0 in |