


## Valuflex®/GS - Green, Yellow, Blue Rubber Hose



Valuflex/GS is one of the finest multi-purpose air and water hose available, anywhere. Valuflex provides job/color coding possibilities for safety and other considerations. Valuflex is a very economical general service air and water hose. It can be used in numerous industrial, agricultural and construction applications where oil is not a factor. Valuflex is easy to handle and very flexible due to its multi-spiral layers of durable reinforcing polyester yarn. Available in a wide variety of sizes, Valuflex provides constant working pressures of 150, 200, 250 or 300 psi. It has an EPDM tube and cover that resists abrasion, heat and ozone. This hose is not for use as a steam hose.

- **Cover Color :** Green, Yellow, Blue
- **Oil Resistance :** Limited
- **Construction :**
  - Tube :** EPDM
  - Cover :** EPDM
  - Reinforcement :** Spiral polyester yarn
- **Temperature Range :** -40°F to 200°F (-40°C to 93°C)
- **Packaging :** Reels

Item #	Nominal I.D.	Nominal O.D.	Reinforcement Spirals	Working Pressure	Min. Bend Radius	Cover Color	Temperature Range
00114806300	3/8 in 9.53 mm	0.72 in 18.26 mm	4	250 psi 1.73 MPa	2.25 in 57.15 mm	Green	-40 to 200°F -40 to 93°C
00114808300	1/2 in 12.7 mm	0.88 in 22.23 mm	4	250 psi 1.73 MPa	3 in 76.20 mm	Green	-40 to 200°F -40 to 93°C
00114808400	1/2 in 12.7 mm	0.88 in 22.23 mm	4	300 psi 2.07 MPa	3 in 76.20 mm	Green	-40 to 200°F -40 to 93°C
00114812500	3/4 in 19.05 mm	1.16 in 29.37 mm	4	250 psi 1.73 MPa	4.5 in 114.30 mm	Green	-40 to 200°F -40 to 93°C
00114812400	3/4 in 19.05 mm	1.16 in 29.37 mm	4	300 psi 2.07 MPa	4.5 in 114.30 mm	Green	-40 to 200°F -40 to 93°C
00114812551	3/4 in 19.05 mm	1.16 in 29.37 mm	4	250 psi 1.73 MPa	4.5 in 114.30 mm	Green	-40 to 200°F -40 to 93°C
00114812455	3/4 in 19.05 mm	1.16 in 29.37 mm	4	300 psi 2.07 MPa	4.5 in 114.30 mm	Green	-40 to 200°F -40 to 93°C
00114816300	1 in 25.4 mm	1.43 in 36.20 mm	4	250 psi 1.73 MPa	7 in 177.80 mm	Green	-40 to 200°F -40 to 93°C
00114816400	1 in 25.4 mm	1.43 in 36.20 mm	4	300 psi 2.07 MPa	7 in 177.80 mm	Green	-40 to 200°F -40 to 93°C
00114912356	3/4 in 19.05 mm	1.16 in 29.37 mm	4	250 psi 1.73 MPa	4.5 in 114.30 mm	Yellow	-40 to 200°F -40 to 93°C
00114912351	3/4 in 19.05 mm	1.16 in 29.37 mm	4	250 psi 1.73 MPa	4.5 in 114.30 mm	Yellow	-40 to 200°F -40 to 93°C
00115008300	1/2 in 12.7 mm	0.88 in 22.23 mm	4	250 psi 1.73 MPa	3 in 76.20 mm	Blue	-40 to 200°F -40 to 93°C
00115012300	3/4 in 19.05 mm	1.16 in 29.37 mm	4	250 psi 1.73 MPa	4.5 in 114.30 mm	Blue	-40 to 200°F -40 to 93°C
00115012355	3/4 in 19.05 mm	1.16 in 29.37 mm	4	250 psi 1.73 MPa	4.5 in 114.30 mm	Blue	-40 to 200°F -40 to 93°C
00115016300	1 in 25.4 mm	1.43 in 36.20 mm	4	250 psi 1.73 MPa	7 in 177.80 mm	Blue	-40 to 200°F -40 to 93°C