

**Mainliner<sup>®</sup> Rubber Hose**



Mainliner is designed to handle the oily mists used to lubricate pneumatic tools. This hose is an excellent choice for use with pneumatic tools throughout the industry. It features a medium oil-resistant tube with multi-spiral polyester reinforcement that keeps it flexible even in extreme temperatures. The durable cover resists abrasion, cracking, weathering and ozone. Mainliner offers constant working pressures of 200, 250 and 300 psi. Mainliner is the quality value choice for a general service hose for oily, pneumatic equipment lubrication.

- **Note: Not recommended for handling fuels.**
- **Cover Color :** Red
- **Oil Resistance :** Medium
- **Construction :**  
 Tube : EPDM, RMA Class C  
 Cover : EPDM - Limited  
 Reinforcement : Spiral polyester yarn
- **Temperature Range :** -40°F to 200°F (-40°C to 93°C)
- **Packaging :** Reels

Item #	Nominal I.D.	Nominal O.D.	Reinforcement Spirals	Working Pressure	Min. Bend Radius	Temperature Range
00225504200	1/4 in 6.35 mm	0.50 in 12.7 mm	2	200 psi 1.38 MPa	1.5 in 38.10 mm	-40 to 200 °F -40 to 93 °C

Item #	Nominal I.D.	Nominal O.D.	Reinforcement Spirals	Working Pressure	Min. Bend Radius	Temperature Range
00225504400	1/4 in 6.35 mm	0.63 in 15.88 mm	4	300 psi 2.07 MPa	1.5 in 38.10 mm	-40 to 200 °F -40 to 93 °C
00225505400	5/16 in 7.94 mm	0.63 in 15.88 mm	4	300 psi 2.07 MPa	2 in 50.80 mm	-40 to 200 °F -40 to 93 °C
00225506200	3/8 in 9.53 mm	0.690 in 17.46 mm	2	200 psi 1.38 MPa	2.25 in 57.15 mm	-40 to 200 °F -40 to 93 °C
00225506400	3/8 in 9.53 mm	0.72 in 18.26 mm	4	300 psi 2.07 MPa	2.25 in 57.15 mm	-40 to 200 °F -40 to 93 °C
00225508200	1/2 in 12.7 mm	0.81 in 20.64 mm	2	200 psi 1.38 MPa	3 in 76.20 mm	-40 to 200 °F -40 to 93 °C
00225508400	1/2 in 12.7 mm	0.88 in 22.23 mm	4	300 psi 2.07 MPa	3 in 76.20 mm	-40 to 200 °F -40 to 93 °C
00225510400	5/8 in 15.88 mm	1 in 25.4 mm	4	300 psi 2.07 MPa	3.75 in 95.25 mm	-40 to 200 °F -40 to 93 °C
00225512300	3/4 in 19.05 mm	1.16 in 29.37 mm	4	250 psi 1.72 MPa	4.5 in 114.30 mm	-40 to 200 °F -40 to 93 °C
00225512351	3/4 in 19.05 mm	1.16 in 29.37 mm	4	250 psi 1.72 MPa	4.5 in 114.30 mm	-40 to 200 °F -40 to 93 °C
00225512400	3/4 in 19.05 mm	1.16 in 29.37 mm	4	300 psi 2.07 MPa	4.5 in 114.30 mm	-40 to 200 °F -40 to 93 °C
00225512451	3/4 in 19.05 mm	1.16 in 29.37 mm	4	300 psi 2.07 MPa	4.5 in 114.30 mm	-40 to 200 °F -40 to 93 °C
00225516200	1 in 25.4 mm	1.43 in 36.20 mm	4	200 psi 1.38 MPa	7 in 177.80 mm	-40 to 200 °F -40 to 93 °C
00225516400	1 in 25.4 mm	1.43 in 36.20 mm	4	300 psi 2.07 MPa	7 in 177.80 mm	-40 to 200 °F -40 to 93 °C
00225520200	1 1/4 in 31.75 mm	1.78 in 47.63 mm	4	200 psi 1.38 MPa	8.75 in 222.25 mm	-40 to 200 °F -40 to 93 °C
00225524200	1 1/2 in 38.1 mm	2.03 in 51.59 mm	4	200 psi 1.38 MPa	10.5 in 266.70 mm	-40 to 200 °F -40 to 93 °C
00225532200	2 in 50.8 mm	2 1/2 in 63.5 mm	4	200 psi 1.38 MPa	14 in 355.60 mm	-40 to 200 °F -40 to 93 °C

**Airflex<sup>™</sup> Rubber Hose**



Airflex hose is the quality choice for any application where a medium oil resistant tube is needed to lubricate air tools. Airflex has a working pressure to 300 psi in a full range of sizes from 1/4" I.D. to 3/4" I.D. It has a highly visible yellow cover that is weather, ozone and abrasion resistant. Airflex has a durable 4-spiral construction to handle abuse oriented applications and a yellow cover for coding applications. Stock the quality choice, the right choice, the highly visible, Airflex hose.

- **Cover Color :** Yellow
- **Oil Resistance :** Medium

- **Construction :**  
 Tube : EPDM, RMA Class C  
 Cover : EPDM - Limited  
 Reinforcement : Spiral polyester yarn
- **Temperature Range :** -40°F to 200°F (-40°C to 93°C)
- **Packaging :** Reels

Item #	Nominal I.D.	Nominal O.D.	Reinforcement Spirals	Working Pressure	Min. Bend Radius	Temperature Range
00235504400	1/4 in 6.35 mm	0.63 in 15.88 mm	4	300 psi 2.07 MPa	1.5 in 38.10 mm	-40 to 200 °F -40 to 93 °C
00235506400	3/8 in 9.53 mm	0.72 in 18.26 mm	4	300 psi 2.07 MPa	2.25 in 57.15 mm	-40 to 200 °F -40 to 93 °C
00235508400	1/2 in 12.7 mm	0.88 in 22.23 mm	4	300 psi 2.07 MPa	3 in 76.20 mm	-40 to 200 °F -40 to 93 °C
00235512400	3/4 in 19.05 mm	1.16 in 29.37 mm	4	300 psi 2.07 MPa	4.5 in 114.30 mm	-40 to 200 °F -40 to 93 °C
00235512451	3/4 in 19.05 mm	1.16 in 29.37 mm	4	300 psi 2.07 MPa	4.5 in 114.30 mm	-40 to 200 °F -40 to 93 °C



OH: 800-344-0150  
GA: 888-492-2140

FAX: 937-454-2086  
FAX: 770-428-0717