

**Dura-Red™ Rubber Hose**



Dura-Red is the premium non-conductive multipurpose hose that handles oil mist, air, water and mild chemicals. Not recommended for fuels. Meets electrical resistance portion of the Alcoa Potroom air and water specs (30.4.2). Dura-Red has 4-spiral, 300 psi construction to handle abuse oriented applications.

- **Cover Color :** Red
- **Oil Resistance :** Medium
- **Construction :** Non-conductive  
**Tube :** EPDM, RMA Class C

**Cover :** EPDM Class C

**Reinforcement :** Spiral polyester yarn

- **Temperature Range :** -40°F to 200°F (-40°C to 93°C)
- **Packaging :** Reels

Item #	Nominal I.D.	Nominal O.D.	Reinforcement Spirals	Working Pressure	Min. Bend Radius	Temperature Range
00275506400	3/8 in 9.53 mm	0.72 in 18.26 mm	4	300 psi 2.07 MPa	2.25 in 57.15 mm	-40 to 200°F -40 to 93°C
00275508400	1/2 in 12.7 mm	0.88 in 22.23 mm	4	300 psi 2.07 MPa	3 in 76.20 mm	-40 to 200°F -40 to 93°C
00275512400	3/4 in 19.05 mm	1.16 in 29.37 mm	4	300 psi 2.07 MPa	4.5 in 114.30 mm	-40 to 200°F -40 to 93°C
00275512451	3/4 in 19.05 mm	1.16 in 29.37 mm	4	300 psi 2.07 MPa	4.5 in 114.30 mm	-40 to 200°F -40 to 93°C
00275516400	1 in 25.4 mm	1.43 in 36.20 mm	4	300 psi 2.07 MPa	7 in 177.80 mm	-40 to 200°F -40 to 93°C
00275520300	1 1/4 in 31.75 mm	1 3/4 in 44.45 mm	4	300 psi 2.07 MPa	8.75 in 222.25 mm	-40 to 200°F -40 to 93°C

**Maxecon/GP Rubber Hose**



Maxecon is an excellent general purpose air and water service hose that can be used by all industries. It is non-conductive and offers a medium-high oil resistance. Maxecon offers dependable and solid performance with two working pressures: 250 or 300 psi in varying sizes up to 1 1/2" I.D. Its durable cover resists abrasion, weathering and ozone. Maxecon's multi-spiral polyester yarn reinforcement makes this hose durable, flexible and helps eliminate kinks. Maxecon is the ideal hose for use in mining, steel or petroleum applications.

- **Cover Color :** Red
- **Oil Resistance :** Cover (Medium) - Tube (High)
- **Construction :** Non-conductive  
**Tube :** Nitrile blend, RMA Class A  
**Cover :** Nitrile blend, RMA Class B  
**Reinforcement :** Spiral polyester yarn
- **Temperature Range :** -20°F to 160°F or 180°F (intermittent) (-29°C to 71°C or 82°C) (intermittent)
- **Packaging :** Reels

Item #	Nominal I.D.	Nominal O.D.	Reinforcement Spirals	Working Pressure	Min. Bend Radius
00336504300	1/4 in 6.35 mm	0.50 in 12.7 mm	2	250 psi 1.72 MPa	1.5 in 38.10 mm
00336504400	1/4 in 6.35 mm	0.59 in 15.08 mm	4	300 psi 2.07 MPa	1.5 in 38.10 mm
00336505300	5/16 in 7.94 mm	0.63 in 15.88 mm	2	250 psi 1.72 MPa	2 in 50.80 mm
00336506300	3/8 in 9.53 mm	0.72 in 18.26 mm	4	250 psi 1.72 MPa	2.25 in 57.15 mm
00336506400	3/8 in 9.53 mm	0.72 in 18.26 mm	4	300 psi 2.07 MPa	2.25 in 57.15 mm
00336508300	1/2 in 12.7 mm	0.88 in 22.23 mm	4	250 psi 1.72 MPa	3 in 76.20 mm
00336508400	1/2 in 12.7 mm	0.88 in 22.23 mm	4	300 psi 2.07 MPa	3 in 76.20 mm
00336510400	5/8 in 15.88 mm	1 in 25.4 mm	4	300 psi 2.07 MPa	3.75 in 95.25 mm
00336512300	3/4 in 19.05 mm	1.16 in 29.37 mm	4	250 psi 1.72 MPa	4.5 in 114.30 mm
00336512400	3/4 in 19.05 mm	1.16 in 29.37 mm	4	300 psi 2.07 MPa	4.5 in 114.30 mm
00336512454	3/4 in 19.05 mm	1.16 in 29.37 mm	4	300 psi 2.07 MPa	4.5 in 114.30 mm
00336516300	1 in 25.4 mm	1.43 in 36.20 mm	4	250 psi 1.72 MPa	7 in 177.80 mm
00336516400	1 in 25.4 mm	1.43 in 36.20 mm	4	300 psi 2.07 MPa	7 in 177.80 mm
00336520300	1 1/4 in 31.75 mm	1.78 in 45.24 mm	4	250 psi 1.72 MPa	8.75 in 222.25 mm
00336524300	1 1/2 in 38.1 mm	2.03 in 51.59 mm	4	250 psi 1.72 MPa	10.5 in 266.70 mm