

Black Max[®] M.R.O. Rubber Hose



This premium quality, non-conductive hose is high in oil resistance throughout. Its fuel line quality will convey oil, fuel oil, diesel, kerosene and other petroleum derived products. Its tough, black cover resists oils and solvents as well as weathering, ozone and abrasion. Hose is tested to have a minimum of 1,000,000 ohms per inch resistance when tested with a 1,000 volt D.C. meggar.

- **Note: Not recommended for a variety of unleaded gasoline.**
- **Cover Color :** Black
- **Oil Resistance :** High

- **Construction :** Non-conductive
Tube : NBR, RMA Class A
Cover : NBR/PVC RMA Class A
Reinforcement : Spiral polyester yarn
- **Temperature Range :** -20°F to 180°F (-29°C to 82°C)
- **Packaging :** Reels

Item #	Nominal I.D.	Nominal O.D.	Reinforcement Spirals	Working Pressure	Min. Bend Radius	Temperature Range
00447604400	1/4 in 6.35 mm	0.63 in 15.88 mm	4	300 psi 2.07 MPa	1.5 in 38.10 mm	-20 to 180 °F -29 to 82 °C
00447606400	3/8 in 9.53 mm	0.72 in 18.26 mm	4	300 psi 2.07 MPa	2.25 in 57.15 mm	-20 to 180 °F -29 to 82 °C
00447608400	1/2 in 12.7 mm	0.91 in 23.02 mm	4	300 psi 2.07 MPa	3 in 76.20 mm	-20 to 180 °F -29 to 82 °C
00447612400	3/4 in 19.05 mm	0.88 in 22.23 mm	4	300 psi 2.07 MPa	4.5 in 114.30 mm	-20 to 180 °F -29 to 82 °C
00447616400	1 in 25.4 mm	1.43 in 36.20 mm	4	300 psi 2.07 MPa	7 in 177.80 mm	-20 to 180 °F -29 to 82 °C

Goldenair[®] Rubber Hose



Goldenair is an excellent general purpose hose for air, petroleum products and nitrogen service. Designed for the harsh conditions found in steel mills, shipyards, foundries, auto plants and construction sites, Goldenair resists weathering, ozone and abrasion. Goldenair provides a constant working pressure to 350 psi in 3/4" size and is kink resistant. This premium quality hose is non-conductive. It has a tough, durable cover that resists oils and other solvents. Its 4-spiral polyester yarn reinforcement provides added strength and flexibility even in the most

extreme conditions.

- **Note: Not recommended for a variety of unleaded gasoline.**
- **Cover Color :** Yellow
- **Oil Resistance :** High
- **Construction :** Non-conductive
Tube : NBR, RMA Class A
Cover : NBR/PVC RMA Class A
Reinforcement : Spiral polyester yarn
- **Temperature Range :** -20°F to 180°F (-29°C to 82°C)
- **Packaging :** Reels

Item #	Nominal I.D.	Nominal O.D.	Reinforcement Spirals	Working Pressure	Min. Bend Radius	Temperature Range
00447312600	3/4 in 19.05 mm	1.16 in 29.37 mm	4	350 psi 2.41 MPa	4.5 in 114.30 mm	-20 to 180 °F -29 to 82 °C
00447316400	1 in 25.4 mm	1.43 in 36.20 mm	4	300 psi 2.07 MPa	7 in 177.80 mm	-20 to 180 °F -29 to 82 °C