

### Green GP/Oxygen Rubber Hose



Green GP/Oxygen hose is designed to handle the harsh, abusive conditions found in steel producing and oil refinery environments. The green cover is commonly color coded for oxygen in mills. It features a medium-high oil resistant NBR blend tube with a 4-spiral polyester yarn reinforcement. The high oil resistant cover and a constant working pressure of 300 psi make this tough, heavy-duty hose the ideal choice for industrial use.

- **Note:** This hose is not recommended for fuel or air breathing

applications.

- **Cover Color :** Green
- **Oil Resistance :** Medium-High
- **Construction :**  
**Tube :** PVC, RMA Class B  
**Cover :** PVC, RMA Class B  
**Reinforcement :** Spiral polyester yarn
- **Temperature Range :** -20°F to 180°F (-29°C to 82°C)
- **Packaging :** Reels

Item #	Nominal I.D.	Nominal O.D.	Reinforcement Spirals	Working Pressure	Min. Bend Radius	Temperature Range
00336606400	3/8 in 9.53 mm	0.88 in 22.23 mm	4	300 psi 2.07 MPa	2.25 in 57.15 mm	-20 to 180 °F -23 to 82 °C
00336608400	1/2 in 12.7 mm	0.94 in 23.81 mm	4	300 psi 2.07 MPa	3 in 76.20 mm	-20 to 180 °F -29 to 82 °C
00336612400	3/4 in 19.05 mm	1.16 in 29.37 mm	4	300 psi 2.07 MPa	4.5 in 114.30 mm	-20 to 180 °F -29 to 82 °C

### Radial Aire Rubber Hose



Radial Aire is a premium, multipurpose PVC air hose used across industry. Radial Aire is a medium-high resistant hose and offers an operating temperature range between -10°F and 150°F. Radial Aire provides smooth, solid performance and offers constant working pressure of 250 or 300 psi. It features a durable PVC cover and tube with a 2-spiral polyester reinforcing cords that help keep the hose kink resistant and flexible.

- **Cover Color :** Blue or Red
- **Oil Resistance :** Medium-High
- **Construction :**  
**Tube :** PVC, RMA Class B  
**Cover :** PVC, RMA Class B  
**Reinforcement :** Spiral polyester yarn
- **Temperature Range :** -10°F to 150°F (-23°C to 66°C)
- **Packaging :** Reels

Item #	Nominal I.D.	Nominal O.D.	Reinforcement Spirals	Working Pressure	Min. Bend Radius	Temperature Range
00134504400	1/4 in 6.35 mm	0.50 in 12.7 mm	2	300 psi 2.07 MPa	1.5 in 38.10 mm	-10 to 150 °F -23 to 66 °C
00134505400	5/16 in 7.94 mm	0.56 in 14.29 mm	2	300 psi 2.07 MPa	2 in 50.80 mm	-10 to 150 °F -23 to 66 °C

Item #	Nominal I.D.	Nominal O.D.	Reinforcement Spirals	Working Pressure	Min. Bend Radius	Temperature Range
00134506400	3/8 in 9.53 mm	0.63 in 15.88 mm	2	300 psi 2.07 MPa	2.25 in 57.15 mm	-10 to 150 °F -23 to 66 °C
00134508400	1/2 in 12.7 mm	0.78 in 19.84 mm	2	300 psi 2.07 MPa	3 in 76.20 mm	-10 to 150 °F -23 to 66 °C
00134510500	5/8 in 15.88 mm	0.91 in 23.02 mm	2	250 psi 1.72 MPa	3.75 in 95.25 mm	-10 to 150 °F -23 to 66 °C
00134512500	3/4 in 19.05 mm	1.030 in 26.19 mm	2	250 psi 1.72 MPa	4.5 in 114.30 mm	-10 to 150 °F -23 to 66 °C
00135004400	1/4 in 6.35 mm	0.50 in 12.7 mm	2	300 psi 2.07 MPa	1.5 in 38.10 mm	-10 to 150 °F -23 to 66 °C
00135005400	5/16 in 7.94 mm	0.56 in 14.29 mm	2	300 psi 2.07 MPa	2 in 50.80 mm	-10 to 150 °F -23 to 66 °C
00135006400	3/8 in 9.53 mm	0.63 in 15.88 mm	2	300 psi 2.07 MPa	2.25 in 57.15 mm	-10 to 150 °F -23 to 66 °C
00135008400	1/2 in 12.7 mm	0.78 in 19.84 mm	2	300 psi 2.07 MPa	3 in 76.20 mm	-10 to 150 °F -23 to 66 °C
00135010500	5/8 in 15.88 mm	0.91 in 23.02 mm	2	250 psi 1.72 MPa	3.75 in 95.25 mm	-10 to 150 °F -23 to 66 °C
00135012500	3/4 in 19.05 mm	1.030 in 26.19 mm	2	250 psi 1.72 MPa	4.5 in 114.30 mm	-10 to 150 °F -23 to 66 °C
00134584425	1/4 in 6.35 mm	N/A	N/A	300 psi 2.07 MPa	1.5 in 38.10 mm	-10 to 150 °F -23 to 66 °C
00134584451	1/4 in 6.35 mm	N/A	N/A	300 psi 2.07 MPa	1.5 in 38.10 mm	-10 to 150 °F -23 to 66 °C
00134586425	3/8 in 9.53 mm	N/A	N/A	300 psi 2.07 MPa	2.25 in 57.15 mm	-10 to 150 °F -23 to 66 °C
00134586451	3/8 in 9.53 mm	N/A	N/A	300 psi 2.07 MPa	2.25 in 57.15 mm	-10 to 150 °F -23 to 66 °C
00135086425	3/8 in 9.53 mm	N/A	N/A	300 psi 2.07 MPa	2.25 in 57.15 mm	-10 to 150 °F -23 to 66 °C
00135086451	3/8 in 9.53 mm	N/A	N/A	300 psi 2.07 MPa	2.25 in 57.15 mm	-10 to 150 °F -23 to 66 °C