

Black Standard Heater & Black OEM Heater SAE 20R3, Class D2 Type Coolant Rubber Hose



Kink-resistant EPDM tube and cover resist cracking and weather checking. Multi-spiral polyester reinforced to stay flexible even in extreme temperatures. Long service life since hoses can withstand the abuse of corrosive additives, ozone and abrasion. Series 4703 is SAE 20R3, Class D2. Series 4709 is standard duty heater hose.

- **Cover Color :** Black
- **Oil Resistance :** Limited
- **Construction :**
 Tube : EPDM
 Cover : EPDM
 Reinforcement : Spiral polyester yarn
- **Temperature Range :** -40°F to 200°F (-40°C to 93°C)
- **Packaging :** Reels

Item #	Item Name	Nominal I.D.	Nominal O.D.	Working Pressure	Min. Bend Radius	Temperature Range
00470308151	SAE 20R3, Class D2 Type Hose	1/2 in 12.7 mm	0.80 in 20.24 mm	62 psi 0.43 MPa	3 in 76.20 mm	-40 to 200 °F -40 to 93 °C
00470310199	SAE 20R3, Class D2 Type Hose	5/8 in 15.88 mm	0.94 in 23.81 mm	62 psi 0.43 MPa	3.75 in 95.25 mm	-40 to 200 °F -40 to 93 °C
00470310151	SAE 20R3, Class D2 Type Hose	5/8 in 15.88 mm	0.94 in 23.81 mm	62 psi 0.43 MPa	3.75 in 95.25 mm	-40 to 200 °F -40 to 93 °C

Item #	Item Name	Nominal I.D.	Nominal O.D.	Working Pressure	Min. Bend Radius	Temperature Range
00470312199	SAE 20R3, Class D2 Type Hose	3/4 in 19.05 mm	1.06 in 26.99 mm	50 psi 0.34 MPa	4.5 in 114.30 mm	-40 to 200 °F -40 to 93 °C
00470312151	SAE 20R3, Class D2 Type Hose	3/4 in 19.05 mm	1.06 in 26.99 mm	50 psi 0.34 MPa	4.5 in 114.30 mm	-40 to 200 °F -40 to 93 °C
00470316199	SAE 20R3, Class D2 Type Hose	1 in 25.4 mm	1.34 in 34.13 mm	44 psi 0.30 MPa	7 in 177.80 mm	-40 to 200 °F -40 to 93 °C
00470316151	SAE 20R3, Class D2 Type Hose	1 in 25.4 mm	1.34 in 34.13 mm	44 psi 0.30 MPa	7 in 177.80 mm	-40 to 200 °F -40 to 93 °C
00470908199	Standard Duty Heater Hose	1/2 in 12.7 mm	0.81 in 20.64 mm	35 psi 0.24 MPa	3 in 76.20 mm	-40 to 200 °F -40 to 93 °C
00470908151	Standard Duty Heater Hose	1/2 in 12.7 mm	0.81 in 20.64 mm	35 psi 0.24 MPa	3 in 76.20 mm	-40 to 200 °F -40 to 93 °C
00470910199	Standard Duty Heater Hose	5/8 in 15.88 mm	0.88 in 22.23 mm	35 psi 0.24 MPa	3.75 in 95.25 mm	-40 to 200 °F -40 to 93 °C
00470910151	Standard Duty Heater Hose	5/8 in 15.88 mm	0.88 in 22.23 mm	35 psi 0.24 MPa	3.75 in 95.25 mm	-40 to 200 °F -40 to 93 °C
00470912199	Standard Duty Heater Hose	3/4 in 19.05 mm	1.030 in 26.19 mm	35 psi 0.24 MPa	4.5 in 114.30 mm	-40 to 200 °F -40 to 93 °C
00470912151	Standard Duty Heater Hose	3/4 in 19.05 mm	1.030 in 26.19 mm	35 psi 0.24 MPa	4.5 in 114.30 mm	-40 to 200 °F -40 to 93 °C
00470916199	Standard Duty Heater Hose	1 in 25.4 mm	1.34 in 34.13 mm	25 psi 0.17 MPa	7 in 177.80 mm	-40 to 200 °F -40 to 93 °C
00470916151	Standard Duty Heater Hose	1 in 25.4 mm	1.34 in 34.13 mm	25 psi 0.17 MPa	7 in 177.80 mm	-40 to 200 °F -40 to 93 °C

Air Brake, Type A - SAE J1402 & DOT FMVSS 106 Coolant Rubber Hose



Air Brake hose is designed for conveying air in truck and trailer brake systems. Truck and trailer manufacturers, aftermarket packagers and wholesalers use this hose. It is certified to meet D.O.T. FMVSS 106 and SAE J1402A requirements. The EPDM tube and cover with the 4-spiral reinforcement make this hose virtually kink proof. This hose is durable enough to handle this safety related application.

- **Cover Color :** Black
- **Oil Resistance :** Limited
- **Construction :**

Tube : EPDM, RMA Class C
 Cover : EPDM, RMA Class C
 Reinforcement : Spiral polyester yarn

- **Temperature Range :** -40°F to 200°F (-40°C to 93°C)
- **Packaging :** Reels

Item #	Nominal I.D.	Nominal O.D.	Reinforcement Spirals	Working Pressure	Min. Bend Radius	Temperature Range
00482106499	3/8 in 9.53 mm	3/4 in 19.05 mm	4	900 psi 6.20 MPa	2.25 in 57.15 mm	-40 to 200 °F -40 to 93 °C
00482106498	3/8 in 9.53 mm	3/4 in 19.05 mm	4	900 psi 6.20 MPa	2.25 in 57.15 mm	-40 to 200 °F -40 to 93 °C
00482106451	3/8 in 9.53 mm	3/4 in 19.05 mm	4	900 psi 6.20 MPa	2.25 in 57.15 mm	-40 to 200 °F -40 to 93 °C
00482108500	1/2 in 12.7 mm	0.88 in 22.23 mm	4	900 psi 6.20 MPa	3 in 76.20 mm	-40 to 200 °F -40 to 93 °C
00482108498	1/2 in 12.7 mm	0.88 in 22.23 mm	4	900 psi 6.20 MPa	3 in 76.20 mm	-40 to 200 °F -40 to 93 °C
00482108451	1/2 in 12.7 mm	0.88 in 22.23 mm	4	900 psi 6.20 MPa	3 in 76.20 mm	-40 to 200 °F -40 to 93 °C