


**2400 Wet Exhaust SAE J2006
Coolant Rubber Hose**



Style 2400 hose is a soft wall hose designed for use as a straight connection in wet exhaust systems on marine gasoline or diesel engines. This hose can also be used in other marine applications such as drains, replacement of metal piping and vibration absorption.

- **Note: Wet Exhaust is not designed for vacuum service.**
- **Cover Color :** Black
- **Oil Resistance :** Medium to Medium-High
- **Construction :**
 - Tube :** NBR/SBR blend
 - Cover :** CR/NBR blend
 - Reinforcement :** Tire cord
- **Temperature Range :** 0°F to 212°F (-18°C to 100°C)

Item #	Nominal I.D.	Nominal O.D.	Plies	Working Pressure	Temperature Range
16240007560	3/4 in 19.05 mm	1 1/4 in 31.75 mm	2	150 psi 1.03 MPa	0 to 212°F -18 to 100°C
16240008760	7/8 in 22.23 mm	1.38 in 35.05 mm	2	150 psi 1.03 MPa	0 to 212°F -18 to 100°C
16240010060	1 in 25.4 mm	1 1/2 in 38.1 mm	2	150 psi 1.03 MPa	0 to 212°F -18 to 100°C
16240010660	1 1/16 in 26.99 mm	1.56 in 39.62 mm	2	150 psi 1.03 MPa	0 to 212°F -18 to 100°C
16240011260	1 1/8 in 28.58 mm	1.63 in 41.4 mm	2	150 psi 1.03 MPa	0 to 212°F -18 to 100°C
16240012560	1 1/4 in 31.75 mm	1 3/4 in 44.45 mm	2	150 psi 1.03 MPa	0 to 212°F -18 to 100°C
16240013160	1 5/16 in 33.34 mm	1.81 in 45.97 mm	2	150 psi 1.03 MPa	0 to 212°F -18 to 100°C
16240015060	1 3/8 in 34.93 mm	2.08 in 52.83 mm	2	150 psi 1.03 MPa	0 to 212°F -18 to 100°C
16240015060	1 1/2 in 38.1 mm	2.20 in 55.88 mm	2	150 psi 1.03 MPa	0 to 212°F -18 to 100°C

Item #	Nominal I.D.	Nominal O.D.	Plies	Working Pressure	Temperature Range
16240016260	1 5/8 in 41.28 mm	2.33 in 59.18 mm	2	150 psi 1.03 MPa	0 to 212°F -18 to 100°C
16240017560	1 3/4 in 44.45 mm	2.45 in 62.23 mm	2	150 psi 1.03 MPa	0 to 212°F -18 to 100°C
16240018760	1 7/8 in 47.63 mm	2.57 in 65.28 mm	2	150 psi 1.03 MPa	0 to 212°F -18 to 100°C
16240020060	2 in 50.8 mm	2.70 in 68.58 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240021260	2 1/8 in 53.98 mm	2.82 in 71.63 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240022560	2 1/4 in 57.15 mm	2.95 in 74.93 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240023760	2 3/8 in 60.33 mm	3.07 in 77.98 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240025060	2 1/2 in 63.5 mm	3.20 in 81.28 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240026260	2 5/8 in 66.68 mm	3.33 in 84.58 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240026260	2 3/4 in 69.85 mm	3.43 in 87.12 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240028760	2 7/8 in 73.03 mm	3.57 in 90.68 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240030060	3 in 76.2 mm	3.70 in 93.98 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240032560	3 1/4 in 82.55 mm	3.95 in 100.33 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240035060	3 1/2 in 88.9 mm	4.20 in 106.68 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240037560	3 3/4 in 95.25 mm	4.45 in 113.03 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240040060	4 in 101.6 mm	4.70 in 119.38 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240045060	4 1/2 in 114.30 mm	5.20 in 132.08 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240050060	5 in 127.0 mm	5.70 in 144.78 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240055060	5 1/2 in 139.70 mm	6.20 in 157.48 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240055660	5 9/16 in 141.29 mm	6.26 in 159.00 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C
16240060060	6 in 152.4 mm	6.26 in 159.00 mm	2	100 psi 0.69 MPa	0 to 212°F -18 to 100°C

**7910 Bellowsflex® #8482; "A"
Coolant, Marine, Fuel Hose**



Type 7910 Bellowsflex hose is an extremely versatile product which has become an industry standard. This multipurpose hose is used in applications where wire reinforcement is required to provide great flexibility and resist kinking. Some of the applications include: bilge ventilation, bilge pump intake and discharge, toilet and bath connections, cabin heating, internal water systems, galleys and drains. This hose

meets SAE J1527 Type A2, USCG 1942F and SAE J2006, R2.

- **Cover Color :** Black
- **Oil Resistance :** High
- **Construction :**
 - Tube :** NBR
 - Cover :** CR
 - Reinforcement :** Nylon Screen with helical wire
- **Temperature Range :** -20°F to 212°F (-29°C to 100°C)

Item #	Nominal I.D.	Nominal O.D.	Plies	Working Pressure	Min. Bend Radius	Temperature Range
16791005025	1/2 in 12.7 mm	0.88 in 22.23 mm	2	60 psi 0.41 MPa	2 in 50.80 mm	-20 to 212°F -29 to 100°C
16791006225	5/8 in 15.88 mm	1 in 25.4 mm	2	60 psi 0.41 MPa	2 in 50.80 mm	-20 to 212°F -29 to 100°C
16791007560	3/4 in 19.05 mm	1.13 in 28.58 mm	2	58 psi 0.40 MPa	3 in 76.20 mm	-20 to 212°F -29 to 100°C