

### 7910 Bellowsflex® #8482; "A" Coolant, Marine, Fuel Hose (cont.)

Item #	Nominal I.D.	Nominal O.D.	Plies	Working Pressure	Min. Bend Radius	Temperature Range
16791008760	7/8 in 22.23 mm	1 1/4 in 31.75 mm	2	55 psi 0.38 MPa	3 in 76.20 mm	-20 to 212 °F -29 to 100 °C
16791010060	1 in 25.4 mm	1.38 in 34.93 mm	2	53 psi 0.37 MPa	3 in 76.20 mm	-20 to 212 °F -29 to 100 °C
16791010660	1 1/16 in 26.99 mm	1.44 in 36.51 mm	2	53 psi 0.37 MPa	3 in 76.20 mm	-20 to 212 °F -29 to 100 °C
16791011260	1 1/8 in 28.58 mm	1 1/2 in 38.1 mm	2	50 psi 0.34 MPa	3 in 76.20 mm	-20 to 212 °F -29 to 100 °C
16791012560	1 1/4 in 31.75 mm	1.63 in 41.28 mm	2	44 psi 0.30 MPa	3 in 76.20 mm	-20 to 212 °F -29 to 100 °C
16791013160	1 5/16 in 33.34 mm	1.69 in 42.86 mm	2	44 psi 0.30 MPa	4 in 101.60 mm	-20 to 212 °F -29 to 100 °C
16791013760	1 3/8 in 34.93 mm	1 3/4 in 44.45 mm	2	44 psi 0.30 MPa	4 in 101.60 mm	-20 to 212 °F -29 to 100 °C
16791015060	1 1/2 in 38.1 mm	1.88 in 47.63 mm	2	44 psi 0.30 MPa	4 in 101.60 mm	-20 to 212 °F -29 to 100 °C
16791016260	1 5/8 in 41.28 mm	2 in 50.8 mm	2	41 psi 0.28 MPa	5 in 127 mm	-20 to 212 °F -29 to 100 °C
16791017560	1 3/4 in 44.45 mm	2.13 in 53.98 mm	2	41 psi 0.28 MPa	5 in 127 mm	-20 to 212 °F -29 to 100 °C
16791018760	1 7/8 in 47.63 mm	2 1/4 in 57.15 mm	2	38 psi 0.26 MPa	5 in 127 mm	-20 to 212 °F -29 to 100 °C
16791020060	2 in 50.8 mm	2.38 in 60.33 mm	2	35 psi 0.24 MPa	6 in 152.40 mm	-20 to 212 °F -29 to 100 °C
16791021260	2 1/8 in 53.98 mm	2 1/2 in 63.5 mm	2	34 psi 0.23 MPa	6 in 152.40 mm	-20 to 212 °F -29 to 100 °C

Item #	Nominal I.D.	Nominal O.D.	Plies	Working Pressure	Min. Bend Radius	Temperature Range
16791022560	2 1/4 in 57.15 mm	2.63 in 66.68 mm	2	34 psi 0.23 MPa	6 in 152.40 mm	-20 to 212 °F -29 to 100 °C
16791023760	2 3/8 in 60.33 mm	2 3/4 in 69.85 mm	2	33 psi 0.23 MPa	7 in 177.80 mm	-20 to 212 °F -29 to 100 °C
16791025060	2 1/2 in 63.5 mm	2.88 in 73.03 mm	2	30 psi 0.21 MPa	8 in 203.20 mm	-20 to 212 °F -29 to 100 °C
16791026260	2 5/8 in 66.68 mm	3 in 76.2 mm	2	30 psi 0.21 MPa	10 in 254 mm	-20 to 212 °F -29 to 100 °C
16791027560	2 3/4 in 69.85 mm	3.13 in 79.38 mm	2	29 psi 0.20 MPa	10 in 254 mm	-20 to 212 °F -29 to 100 °C
16791028760	2 7/8 in 73.03 mm	3 1/4 in 82.55 mm	2	29 psi 0.20 MPa	11 in 279.40 mm	-20 to 212 °F -29 to 100 °C
16791030060	3 in 76.2 mm	3.38 in 85.73 mm	2	26 psi 0.18 MPa	13 in 330.20 mm	-20 to 212 °F -29 to 100 °C
16791031260	3 1/8 in 79.38 mm	3 1/2 in 88.9 mm	2	23 psi 0.16 MPa	13 in 330.20 mm	-20 to 212 °F -29 to 100 °C
16791032560	3 1/4 in 82.55 mm	3.63 in 92.08 mm	2	21 psi 0.14 MPa	14 in 355.60 mm	-20 to 212 °F -29 to 100 °C
16791035060	3 1/2 in 88.9 mm	3.88 in 98.43 mm	2	20 psi 0.14 MPa	14 in 355.60 mm	-20 to 212 °F -29 to 100 °C
16791040060	4 in 101.6 mm	4.38 in 111.13 mm	2	18 psi 0.12 MPa	15 in 381.00 mm	-20 to 212 °F -29 to 100 °C
16791045060	4 1/2 in 114.30 mm	4.88 in 123.83 mm	2	16 psi 0.11 MPa	16 in 406.40 mm	-20 to 212 °F -29 to 100 °C
16791050060	5 in 127.0 mm	5.38 in 136.53 mm	2	14 psi 0.10 MPa	28 in 711.20 mm	-20 to 212 °F -29 to 100 °C
16791055060	5 1/2 in 139.70 mm	5.88 in 149.23 mm	2	13 psi 0.09 MPa	31 in 787.40 mm	-20 to 212 °F -29 to 100 °C
16791060060	6 in 152.4 mm	6.38 in 161.93 mm	2	11 psi 0.08 MPa	33 in 838.20 mm	-20 to 212 °F -29 to 100 °C

### 2428 Mariner Premium Wet Exhaust SAE J2006 Coolant Rubber Hose



Tube: NBR/SBR.

- **Reinforcement:** Tire Cord.
- **Cover:** CR/NBR.
- **Temperature :** 0° to +212°F
- **Length:** 12 & 60 ft.
- **Branding:** Blue Layline Thermoid Mariner Wet Exhaust SAE J2006R1 Date, Made In USA
- **Cut Lengths:** Contact Customer Service. Standard Case. 5% Cutting Charge.

Item #	Tube	Temperature Range	Nominal I.D.	Nominal O.D.	Working Pressure
16242807560	NBR/SBR	0 to 212 °F	3/4 in	1 3/8 in	200 psi
16242808760	NBR/SBR	0 to 212 °F	7/8 in	1 1/2 in	200 psi
16242810060	NBR/SBR	0 to 212 °F	1 in	1 5/8 in	200 psi
16242810660	NBR/SBR	0 to 212 °F	1 1/16 in	1 11/16 in	200 psi
16242811260	NBR/SBR	0 to 212 °F	1 1/8 in	1 3/4 in	200 psi
16242812560	NBR/SBR	0 to 212 °F	1 1/4 in	1 7/8 in	200 psi

Item #	Tube	Temperature Range	Nominal I.D.	Nominal O.D.	Working Pressure
16242813160	NBR/SBR	0 to 212 °F	1 5/16 in	1 15/16 in	200 psi
16242813760	NBR/SBR	0 to 212 °F	1 3/8 in	2 in	200 psi
16242815060	NBR/SBR	0 to 212 °F	1 1/2 in	2 1/8 in	200 psi
16242816260	NBR/SBR	0 to 212 °F	1 5/8 in	2 1/4 in	200 psi
16242817560	NBR/SBR	0 to 212 °F	1 3/4 in	2 3/8 in	200 psi
16242818760	NBR/SBR	0 to 212 °F	1 7/8 in	2 1/2 in	200 psi
16242820060	NBR/SBR	0 to 212 °F	2 in	2 5/8 in	200 psi
16242821260	NBR/SBR	0 to 212 °F	2 1/8 in	2 3/4 in	200 psi
16242822560	NBR/SBR	0 to 212 °F	2 1/4 in	2 7/8 in	200 psi
16242823760	NBR/SBR	0 to 212 °F	2 3/8 in	3 in	175 psi
16242825060	NBR/SBR	0 to 212 °F	2 1/2 in	3 1/4 in	175 psi
16242826260	NBR/SBR	0 to 212 °F	2 5/8 in	3 3/8 in	175 psi
16242827560	NBR/SBR	0 to 212 °F	2 3/4 in	3 1/2 in	175 psi
16242828760	NBR/SBR	0 to 212 °F	2 7/8 in	3 5/8 in	175 psi
16242830060	NBR/SBR	0 to 212 °F	3 in	3 3/4 in	150 psi
16242831260	NBR/SBR	0 to 212 °F	3 1/8 in	3 7/8 in	150 psi
16242832560	NBR/SBR	0 to 212 °F	3 1/4 in	4 in	150 psi
16242835060	NBR/SBR	0 to 212 °F	3 1/2 in	4 1/4 in	150 psi
16242837560	NBR/SBR	0 to 212 °F	3 3/4 in	4.50 in	150 psi
16242840060	NBR/SBR	0 to 212 °F	4 in	4 3/4 in	150 psi
16242845060	NBR/SBR	0 to 212 °F	4 1/2 in	5 1/4 in	150 psi
16242850060	NBR/SBR	0 to 212 °F	5 in	5.75 in	150 psi
16242855060	NBR/SBR	0 to 212 °F	5 1/2 in	6 1/4 in	150 psi
16242860060	NBR/SBR	0 to 212 °F	6 in	6 5/8 in	150 psi



OH: 800-344-0150  
GA: 888-492-2140

FAX: 937-454-2086  
FAX: 770-428-0717