

White Food Transfer Hose



Application

- Liquid, fatty and oily food and alcoholic beverage suction and delivery.
- Hose may be sterilized with 30 PSI steam at 266°F for 30 minutes maximum - open end only.
- Not recommended for dry abrasive materials.
- **Cover**
- Non-marking white, NBR/PVC blended rubber.
- **Reinforcement**
- Spiraled high tensile textile cords, and 4 highly flexible steel helix wires.

- **Tube**
- White NBR. Meets FDA and 3A requirements.
- **Branding**
- ALFAGOMMA - ITALY T405 10 BAR (150 PSI) - GENERAL PURPOSE FOOD QUALITY - S & D (black letters)

Item #	Nominal I.D.	Nominal O.D.	Working Pressure	Min. Bend Radius	Temperature Range
T405LL100	1 in 25 mm	1.46 in 37 mm	150 psi 10 bar	3 in	-22 to 176 °F
T405LL150	1 1/2 in 38 mm	1.97 in 50 mm	150 psi 10 bar	4 in	-22 to 176 °F
T405LL200	2 in 51 mm	2.48 in 63 mm	150 psi 10 bar	6 in	-22 to 176 °F
T405LL300	3 in 76 mm	3.46 in 88 mm	150 psi 10 bar	9 in	-22 to 176 °F
T405LL400	4 in 102 mm	4.57 in 116 mm	150 psi 10 bar	12 in	-22 to 176 °F

Grey Food Transfer Hose



Application

- Liquid, fatty and oily food and alcoholic beverage suction and delivery. Hose may be sterilized with 30 PSI steam at 266°F for 30 minutes maximum - open end only. Not recommended for dry abrasive materials.

- **Cover** Grey NBR/PVC blended rubber.
- **Reinforcement**
- Spiraled high tensile textile cords, and 4 highly flexible steel helix wires.
- **Tube**
- White NBR. Meets FDA and 3A requirements.
- **Branding**
- ALFAGOMMA - ITALY T405 10 BAR (150 PSI) - GENERAL PURPOSE FOOD QUALITY - S & D (black letters)

Item #	Nominal I.D.	Nominal O.D.	Working Pressure	Min. Bend Radius	Temperature Range
T405LB200	2 in 51 mm	2.56 in 65 mm	150 psi 10 bar	8 in	-22 to 176 °F
T405LB300	3 in 76 mm	3.54 in 90 mm	150 psi 10 bar	12 in	-22 to 176 °F

Food and Beverage Suction and Discharge Hose



Application

- Food and alcoholic beverage suction and discharge. Specially designed for oil-based foods, wine, beer and spirits, up to 95 proof. Hose may be sterilized with 30 PSI steam at 266°F for 30 minutes maximum - open end only. Not recommended for dry abrasive materials.
- **Cover**
- White EPDM - abrasion and ozone resistant
- **Reinforcement**

- High tensile textile cords with embedded nylon helix.
- **Tube** White, nontoxic chlorobutyl rubber. Meets FDA and 3A requirements.
- **Temperature Range** -22°F (-30°C) to 176°F (+80°C)
- **Branding** ALFAGOMMA - ITALY T408 16 BAR (240 PSI) - ALL FOOD SUCTION & DELIVERY (in black letters).
- **Coupling Suggestions** Cam and groove couplings attached with bands

Item #	I.D.	O.D.	Min. Bend Radius	Temperature Range	Weight
T408LL100	1 in 25.4 mm	1.46 in 37 mm	5 in	-22 to 176 °F -30 to 80 °C	.58 lb/100 ft
T408LL150	1 1/2 in 38.1 mm	2.05 in 52 mm	7 1/2 in	-22 to 176 °F -30 to 80 °C	.99 lb/100 ft
T408LL200	2 in 50.8 mm	2.64 in 67 mm	10 in	-22 to 176 °F -30 to 80 °C	1.49 lb/100 ft
T408LL300	3 in 76.2 mm	3.70 in 94 mm	15 in	-22 to 176 °F -30 to 80 °C	2.25 lb/100 ft