

Type 75 Butane-Propane Thermocure Hose



Type 75 Butane-Propane hose is specifically designed for transferring liquefied propane gas from bulk storage tank cars or cylinders or from bobtails trucks to home storage tanks. The black cover on the Type 75 hose resists oil, snagging and abrasion. This hose has been pin-pricked to permit gas diffusion. The cover is smooth, making it a driver's choice. This hose has multi-spiral, high tensile reinforcement providing maximum strength and flexibility. It is engineered for a minimum burst of 1750 pounds for the ultimate in safety. A variety of Type 75 hose sizes can be ordered in coupled lengths (M x M) complete with Thermoid's PRO-SUR Brass Fittings (D.O.T Test Certificate included).

- **Note : Do not use reusable couplings with this product. This hose is intentionally pin-pricked for safety reasons. Type 75 Butane-Propane hose must be used in an open, well-ventilated environment.**
- **Cover Color :** Black
- **Oil Resistance :** High, Medium-High
- **Construction :**
 - Tube :** NBR, RMA Class A
 - Cover :** CM, RMA Class B
 - Reinforcement :** 2 or 4 spiral polyester yarn
- **Temperature Range :** -40°F to +180°F (-40°C to +82°C)
- **Packaging :** Reels

Item #	Nominal I.D.	Nominal O.D.	Reinforcement Spirals	Working Pressure	Min. Bend Radius	Temperature Range
22072161662	1/4 in 6.35 mm	0.58 in 14.68 mm	2	350 psi 2.41 MPa	1.5 in 38.10 mm	-40 to 180 °F -40 to 82 °C
22074161662	1/4 in 6.35 mm	0.63 in 15.88 mm	4	350 psi 2.41 MPa	1.5 in 38.10 mm	-40 to 180 °F -40 to 82 °C
22072241662	3/8 in 9.53 mm	0.690 in 17.46 mm	2	350 psi 2.41 MPa	2.25 in 57.15 mm	-40 to 180 °F -40 to 82 °C
22074241662	3/8 in 9.53 mm	3/4 in 19.05 mm	4	350 psi 2.41 MPa	2.25 in 57.15 mm	-40 to 180 °F -40 to 82 °C
22074321662	1/2 in 12.7 mm	0.94 in 23.81 mm	4	350 psi 2.41 MPa	3 in 76.20 mm	-40 to 180 °F -40 to 82 °C
22074481662	3/4 in 19.05 mm	1 1/4 in 31.75 mm	4	350 psi 2.41 MPa	4.5 in 114.30 mm	-40 to 180 °F -40 to 82 °C
22074641662	1 in 25.4 mm	1 1/2 in 38.1 mm	4	350 psi 2.41 MPa	7 in 177.80 mm	-40 to 180 °F -40 to 82 °C
22074481101	3/4 in 19.05 mm	N/A	4	350 psi 2.41 MPa	4.5 in 114.30 mm	-40 to 180 °F -40 to 82 °C
22074481121	3/4 in 19.05 mm	N/A	4	350 psi 2.41 MPa	4.5 in 114.30 mm	-40 to 180 °F -40 to 82 °C
22074481151	3/4 in 19.05 mm	N/A	4	350 psi 2.41 MPa	4.5 in 114.30 mm	-40 to 180 °F -40 to 82 °C
22074481171	3/4 in 19.05 mm	N/A	4	350 psi 2.41 MPa	4.5 in 114.30 mm	-40 to 180 °F -40 to 82 °C
22074641101	1 in 25.4 mm	N/A	4	350 psi 2.41 MPa	7 in 177.80 mm	-40 to 180 °F -40 to 82 °C
22074641121	1 in 25.4 mm	N/A	4	350 psi 2.41 MPa	7 in 177.80 mm	-40 to 180 °F -40 to 82 °C
22074641151	1 in 25.4 mm	N/A	4	350 psi 2.41 MPa	7 in 177.80 mm	-40 to 180 °F -40 to 82 °C
22074641171	1 in 25.4 mm	N/A	4	350 psi 2.41 MPa	7 in 177.80 mm	-40 to 180 °F -40 to 82 °C