

**Plaster, Grout and Concrete Hose****Application**

- Designed for pumping plaster, grout, wet cement to construction placement sites at rated pressures.

**Cover**

- Black - SBR/Natural Rubber
- Blue - SBR/EPDM

**Reinforcement**

- Spiraled high tensile textile cords.


**Tube**

- Black conductive NR - abrasion-resistant.

**Branding**

- ALFAGOMMA - ITALY T758 - 55 BAR (800 PSI) PLASTER & CONCRETE (in white letters)

Item #	Nominal I.D.	Nominal O.D.	Working Pressure	Temperature Range
T758AA100	1 in 25 mm	1.57 in 40 mm	800 psi 55 bar	-22 to 176 °F
T758AA125	1 1/4 in 32 mm	1.93 in 49.0 mm	800 psi 55 bar	-22 to 176 °F
T758AA150	1 1/2 in 38 mm	2.28 in 58 mm	800 psi 55 bar	-22 to 176 °F
T758AA200	2 in 51 mm	2.80 in 71 mm	800 psi 55 bar	-22 to 176 °F
T758AE100	1 in 25 mm	1.57 in 40 mm	800 psi 55 bar	-22 to 176 °F
T758AE125	1 1/4 in 32 mm	1.93 in 49.0 mm	800 psi 55 bar	-22 to 176 °F
T758AE150	1 1/2 in 38 mm	2.28 in 58 mm	800 psi 55 bar	-22 to 176 °F
T758AE200	2 in 51 mm	2.80 in 71 mm	800 psi 55 bar	-22 to 176 °F

**High Performance Steel-Reinforced Concrete Pumping Hose****Application**

- Steel-reinforced concrete pumping hose - Special easy handling construction for concrete placement at casting site.

**Cover**

- Black conductive SBR/NR blend - abrasion and ozone resistant.

**Reinforcement**

- High tensile steel cords.

**Tube**

- Black conductive NR - abrasion resistant.

**Branding**

- ALFAGOMMA - ITALY T740 85 BAR (1275 PSI) W. P. HEAVY DUTY CONCRETE PUMPING (in white letters)

Item #	Nominal I.D.	Nominal O.D.	Working Pressure	Wall Thickness	Min. Bend Radius	Temperature Range
T740AA200	2 in 51 mm	2.68 in 69 mm	1275 psi 85 bar	9 mm	10 in	-22 to 176 °F
T740AA250	2 1/2 in 63 mm	3.35 in 85 mm	1275 psi 85 bar	11 mm	10 in	-22 to 176 °F
T740AA300	3 in 76 mm	3.94 in 100 mm	1275 psi 85 bar	12 mm	15 in	-22 to 176 °F
T740AA400	4 in 102 mm	5.04 in 128 mm	1275 psi 85 bar	13 mm	20 in	-22 to 176 °F
T740AA500	5 in 127.0 mm	6.10 in 155 mm	1275 psi 85 bar	14 mm	25 in	-22 to 176 °F