


Gunite Hose Series 4310**Applications**

- For convenience of sand and cement to mixing gun
- **Tube**
- 1/4" thick pure gum rubber, tan color

Cover

- EPDM, pin-pricked, tan
- **Features:** Superior abrasion resistant. The non marking cover allows for work around buildings and pool tiles

Reinforcement

- Synthetic fabric with incorporated static wire

Temperature

- -40°F (-40°C) to 185°F (85°C)

Item #	Nominal I.D.	Nominal O.D.	Plies	Working Pressure	Temperature Range	Approx. Weight per Feet	Min. Bend Radius
4310-0150	1 1/2 in 38.1 mm	2.38 in 60.33 mm	2	150 psi 10.34 bar	-40 to 185 °F	1.10 lb.	15 in 380 mm
4310-0163	1 5/8 in 41.28 mm	2.5 in 63.5 mm	2	150 psi 10.34 bar	-40 to 185 °F	1.23 lb.	16.5 in 420 mm
4310-0175	1 3/4 in 44.45 mm	2.63 in 66.68 mm	2	150 psi 10.34 bar	-40 to 185 °F	1.52 lb.	17.5 in 445 mm
4310-0200	2 in 50.8 mm	2.88 in 72.9 mm	2	150 psi 10.34 bar	-40 to 185 °F	1.65 lb.	20 in 508 mm
4310-0250	2 1/2 in 63.5 mm	3.88 in 98.30 mm	2	150 psi 10.34 bar	-40 to 185 °F	2.30 lb.	25 in 635 mm

Light Weight Dry Powder Delivery Hose**Application**

- Discharge of dry powders under low pressure, such as cement, grains and animal feed transfer.

Cover

- Black conductive SBR/NR blend - abrasion and ozone resistant.

Reinforcement

- Spiraled high tensile textile cords.

Tube

- 3/16" thick black static conducting natural rubber, compounded to resist cutting by abrasive materials.

Branding

- ALFAGOMMA - ITALY T760 5 BAR (75 PSI) BULK MATERIAL DELIVERY (in white letters)
- Excessive bending during operation may cause premature wear.

Item #	Nominal I.D.	Nominal O.D.	Working Pressure	Temperature Range
T760AA400	4 in 102 mm	4.53 in 115 mm	75 psi 5 bar	-22 to 176 °F