

### Biofuel Petroleum Suction & Discharge Hose



For suction and discharge applications in truck and tank car transfer of gasoline, oil and Biofuels - up to E98 and B100 (T629 is not recommended for use on a reel.) with up to 60% aromatic content at ambient temperature.

Item #	Nominal I.D.	Nominal O.D.	Min. Bend Radius	Approx. Weight per Feet	Working Pressure	Temperature Range
T629AA075X100	3/4 in 19.0 mm	1.14 in 29 mm	3 in	.41 lb.	150 psi	-22 to 176 °F -30 to 80 °C
T629AA100X100	1 in 25 mm	1.38 in 35 mm	4 in	.51 lb.	150 psi	-22 to 176 °F -30 to 80 °C
T629AA125X100	1 1/4 in 32 mm	1.65 in 42 mm	5 in	.60 lb.	150 psi	-22 to 176 °F -30 to 80 °C
T629AA150X100	1 1/2 in 38 mm	1.89 in 48 mm	6 in	.70 lb.	150 psi	-22 to 176 °F -30 to 80 °C
T629AA200X100	2 in 51 mm	2.40 in 61.0 mm	8 in	.91 lb.	150 psi	-22 to 176 °F -30 to 80 °C
T629AA250X100	2 1/2 in 63 mm	2.95 in 75 mm	10 in	1.42 lb.	150 psi	-22 to 176 °F -30 to 80 °C
T629AA300X100	3 in 76 mm	3.46 in 88 mm	12 in	1.69 lb.	150 psi	-22 to 176 °F -30 to 80 °C
T629AA400X100	4 in 102 mm	4.57 in 116 mm	16 in	2.34 lb.	150 psi	-22 to 176 °F -30 to 80 °C

### T650AH 150 PSI Oil Discharge Hose



Application: Oil discharge hose designed for use on trucks, docks or barges where a soft wall hose is required. Cover: Red CR - abrasion, ozone and hydrocarbon resistant. Reinforcement: Spiralled high tensile textile cords with embedded grounding wire. Grounding Wire: Physically extract the ground wire from the hose and bond to the metal coupling, or by other means, to ground. Tube: Black nitrile rubber for 50% aromatics. Temperature Range: -22°F (-30°C) to 176°F (+80°C) Branding: ALFAGOMMA - ITALY T650 10 BAR (150 PSI) - PETROLEUM DELIVERY (in yellow letters). Coupling Suggestions: Cam and groove or combination nipples attached with bands.

Item #	Series	Branding	Nominal I.D.	Nominal O.D.	Working Pressure at 68°F	Length	Approx. Weight per Feet	Temperature Range
T650AH150X100	T650AH	Alfagomma®	1 1/2 in 38.1 mm	1.89 in 48 mm	150 psi	100 ft	0.62 lb.	-22 to 176 °F -30 to 80 °C
T650AH200X100	T650AH	Alfagomma®	2 in 50.8 mm	2.40 in 61.0 mm	150 psi	100 ft	0.81 lb.	-22 to 176 °F -30 to 80 °C
T650AH300X100	T650AH	Alfagomma®	3 in 50.8 mm	3.46 in 88 mm	150 psi	100 ft	1.42 lb.	-22 to 176 °F -30 to 80 °C
T650AH400X100	T650AH	Alfagomma®	4 in 101.6 mm	4.49 in 114.0 mm	150 psi	100 ft	1.92 lb.	-22 to 176 °F -30 to 80 °C