

Cobra™ Fuel Oil Delivery Hose

Cobra Fuel Oil Delivery hose is designed for the delivery and transfer of fuels, oils, commercial gasoline, diesel, kerosene and related petroleum-based products for home delivery, marine, commercial and industrial service. It features an NBR/PVC cover with multiple spiral polyester reinforcement. This unique spiral construction adds strength and flexibility to the hose while making it easy to handle and kink resistant. The smooth, durable cover resists oil and abrasion and is less resistant to dragging, making it the driver's choice. This hose provides top performance and offers a constant working pressure of 250 psi in all sizes.

- **Note :** A static wire is included on all sizes as a safety precaution.

- **Cover Color :** Red
- **Oil Resistance :** High
- **Construction :**
 - Tube :** NBR, RMA Class
 - Cover :** NBR/PVC, RMA Class A
 - Reinforcement :** High tensile spiral polyester cord
- **Temperature Range :** -40°F to +180°F (-40°C to +82°C)
- **Packaging :** Reels

Item #	Nominal I.D.	Nominal O.D.	Plies	Working Pressure	Min. Bend Radius	Temperature Range
22564642662	1 in 25.4 mm	1 1/2 in 38.1 mm	4	250 psi 1.72 MPa	7 in 177.80 mm	-40 to 180 °F -40 to 82 °C
22564802662	1 1/4 in 31.75 mm	1.78 in 45.24 mm	4	250 psi 1.72 MPa	8.75 in 222.25 mm	-40 to 180 °F -40 to 82 °C
22564882662	1 3/8 in 34.93 mm	1.88 in 47.63 mm	4	250 psi 1.72 MPa	9.25 in 234.95 mm	-40 to 180 °F -40 to 82 °C
22564962662	1 1/2 in 38.1 mm	2.09 in 53.18 mm	4	250 psi 1.72 MPa	10.5 in 266.70 mm	-40 to 180 °F -40 to 82 °C

Pumpflex® I - Softwall Hose

Pumpflex I is designed for curb pump self-service stations and highly sensitive electronic fuel pumps. Pumpflex I is the longest lasting automotive refueling hose in use at service stations today. The durable construction of this hose resists deterioration from fuel in the tube. The cover stands up to the ravages of ozone and sunlight. Many hoses fail from cracking behind the nozzle end coupling within two to three years, but Pumpflex I will last longer under normal circumstances. Thermoid continues to use industry standard permanent chrome-plated brass couplings, while others do not. When you need a hose, use the best : Pumpflex I.

- **Note :** Do not use reusable couplings with this product.
- **Cover Color :** Black
- **Oil Resistance :** High, Medium-High
- **Construction :**
 - Tube :** NBR/PVC, RMA Class A
 - Cover :** Thermalon® 8482, U/L approved, Class B
 - Reinforcement :** Spiral polyester cord with static wire (Softwall)
- **Temperature Range :** -40°F to +180°F (-40°C to +82°C)
- **Packaging :** Reels

Item #	Nominal I.D.	Nominal O.D.	Plies	Working Pressure	Min. Bend Radius	Temperature Range
22462401662	5/8 in 15.88 mm	1.030 in 26.19 mm	2	200 psi 1.38 MPa	3.75 in 95.25 mm	-40 to 180 °F -40 to 82 °C
22462481662	3/4 in 19.05 mm	1.13 in 28.58 mm	2	200 psi 1.38 MPa	4.5 in 114.30 mm	-40 to 180 °F -40 to 82 °C
22464641662	1 in 25.4 mm	1 1/2 in 38.1 mm	2	150 psi 1.03 MPa	7 in 177.80 mm	-40 to 180 °F -40 to 82 °C