

**Transporter® Black Tank Truck Hose**

The Transporter Black Tank Truck hose is rated at full vacuum. Like the red version, this hose is recommended for most hydrocarbons with aromatic content up to 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals. The black NBR tube has high oil resistance. The NBR/PVC cover is both oil and abrasion resistant.

- **Cover Color** : Black
- **Oil Resistance** : High
- **Construction** :
  - Tube** : NBR, RMA Class A
  - Cover** : NBR/PVC, RMA Class B

**Reinforcement** : Spiral steel wire helix (es) between synthetic textile plies

- **Temperature Range** : -30°F to +200°F (-34°C to +93°C)

Item #	Nominal I.D.	Nominal O.D.	Plies	Working Pressure	Min. Bend Radius	Temperature Range
17811008002	1 in 25.4 mm	1 1/2 in 38.1 mm	2	200 psi 1.38 MPa	2.5 in 63.50 mm	-30 to 200°F -34 to 93°C
17811010002	1 1/4 in 31.75 mm	1 3/4 in 44.45 mm	2	200 psi 1.38 MPa	3 in 76.20 mm	-30 to 200°F -34 to 93°C
17811015002	1 1/2 in 38.1 mm	2 in 50.8 mm	2	150 psi 1.03 MPa	4.5 in 114.30 mm	-30 to 200°F -34 to 93°C
17811020002	2 in 50.8 mm	2.47 in 62.71 mm	2	150 psi 1.03 MPa	6 in 152.40 mm	-30 to 200°F -34 to 93°C
17811025002	2 1/2 in 63.5 mm	3.06 in 77.79 mm	2	150 psi 1.03 MPa	7.50 in 190.50 mm	-30 to 200°F -34 to 93°C
17811030002	3 in 76.2 mm	3.56 in 90.49 mm	2	150 psi 1.03 MPa	9 in 228.60 mm	-30 to 200°F -34 to 93°C
17811040002	4 in 101.6 mm	4.63 in 117.48 mm	2	150 psi 1.03 MPa	12 in 304.80 mm	-30 to 200°F -34 to 93°C
17811060002	6 in 152.4 mm	6.78 in 172.24 mm	2	100 psi 0.69 MPa	30 in 762.00 mm	-30 to 200°F -34 to 93°C

**Transporter® Flex-Devil™ Hose**

Flex-Devil is a transfer hose for gasoline, a wide range of oils and chemicals and petroleum based products. Flex-devil is made from special rubber compounds that produce an exceptional lightweight and

flexible hose for use in temperatures down to -40 deg F. Rated at FULL VACUUM, Flex-Devil is compatible with gasoline grades up to 50% aromatic content and MTBE/unleaded blends up to 15% MTBE. This hose accepts a range of coupling types: swaged, crimped, internally expanded or banded shank.

Item #	Length	Nominal I.D.	Nominal O.D.	Working Pressure	Min. Bend Radius
17814532002	100 ft	2 in	2.43 in	150 psi	4.0 in
17814534002	100 ft	3 in	3.47 in	150 psi	6.0 in
17814536002	100 ft	4 in	4.54 in	150 psi	2.24 in

**Type 924 Petroleum Transfer Hose**

Type 924 Petroleum Transfer hose is perfect for those applications for the bulk transfer of petroleum products. This hose can also be used to handle most hydrocarbons with aromatic content of 55% maximum, fats, greases, animal oil, vegetable oil, hydraulic fluid and a wide range of chemicals. The black NBR tube has excellent resistants to oil. The cover

compound of NBR/PVC is both oil and abrasion resistant. This hose is rated at FULL VACUUM!

Item #	Nominal I.D.	Nominal O.D.	Working Pressure	Min. Bend Radius
17812008002	1 in	1 1/2 in	200 psi	2.5 in
17812010002	1 1/4 in	1 3/4 in	200 psi	3.0 in
17812015002	1 1/2 in	2 in	150 psi	4.5 in
17812020002	2 in	2 15/32 in	150 psi	6.0 in
17812025002	2 1/2 in	3 1/16 in	150 psi	7.5 in
17812030002	3 in	3 9/16 in	150 psi	9.0 in
17812040002	4 in	4 5/8 in	150 psi	12.0 in
17774456002	6 in	6 3/4 in	100 psi	30.0 in