

Alfajet 210 Pressure Washer Hose



Single wire braid light weight cleaning hose on easy-to-handle reels
Construction :

- **Tube** - Synthetic rubber, black hot water-resistant.
 - **Reinforcement** - High tensile steel wire braid.
 - **Cover** - Synthetic rubber, black or blue weather-, oil-, ozone- and abrasion-resistant.
 - **Couplings** - Standard fittings and AlfaCrimp.
 - **Branding** - ALFAGOMMA ALFAJET 210 ID DN 210 Bar WP - 155°C.
- Temperature Range :** -40° F (-40° C) to 300° F (155° C) constant operation.
- **Maximum Operating Temperature :** 300° F (155° C).

- **Air Maximum Temperature :** 175° F (80° C).
- Operating temperatures in excess of 300° F (155° C) may materially reduce the life of the hose.

Freight : Hydraulic Hose can be combined with other KOA products for qualifying prepaid freight orders.

Item #	I.D.	O.D.	Working Pressure	Min. Bend Radius	Temperature Range	Material Conveyed
T8B3AA-04	1/4 in 6.4 mm	0.48 in 12.1 mm	3000 psi	2 in 50 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B3AA-05	5/16 in 7.9 mm	0.56 in 14.1 mm	3000 psi	2.4 in 60 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B3AA-06	3/8 in 9.5 mm	0.61 in 15.6 mm	3000 psi	2.6 in 65 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B3AA-08	1/2 in 12.7 mm	0.77 in 19.5 mm	3000 psi	3.6 in 90 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B3AE-04	1/4 in 6.4 mm	0.48 in 12.1 mm	3000 psi	2 in 50 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B3AE-05	5/16 in 7.9 mm	0.56 in 14.1 mm	3000 psi	2.4 in 60 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B3AE-06	3/8 in 9.5 mm	0.61 in 15.6 mm	3000 psi	2.6 in 65 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B3AE-08	1/2 in 12.7 mm	0.77 in 19.5 mm	3000 psi	3.6 in 90 mm	-40 to 300 °F -40 to 155 °C	Air Water

Alfajet 400 Pressure Washer Hose



Double wire braid light weight cleaning hose on easy-to-handle reels
Construction :

- **Tube** - Synthetic rubber, black hot water-resistant.
 - **Reinforcement** - Two high tensile steel wire braids.
 - **Cover** - Synthetic rubber, black or blue weather-, oil-, ozone- and abrasion-resistant.
 - **Couplings** - Standard fittings and AlfaCrimp.
 - **Branding** - ALFAGOMMA ALFAJET 400 ID DN Bar WP - 155°C.
- Temperature Range :** -40° F (-40° C) to 300° F (155° C) constant operation.
- **Maximum Operating Temperature :** 300° F (155° C).

- **Air Maximum Temperature :** 175° F (80° C).
- Operating temperatures in excess of 300° F (155° C) may materially reduce the life of the hose.

Freight : Hydraulic Hose can be combined with other KOA products for qualifying prepaid freight orders.

Item #	I.D.	O.D.	Working Pressure	Min. Bend Radius	Temperature Range	Material Conveyed
T8B4AA-04	1/4 in 6.4 mm	0.53 in 13.4 mm	5800 psi	2.8 in 70 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B4AA-05	5/16 in 7.9 mm	0.59 in 15 mm	5800 psi	3 in 76 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B4AA-06	3/8 in 9.5 mm	0.690 in 17.4 mm	5800 psi	3.6 in 90 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B4AA-08	1/2 in 12.7 mm	0.81 in 20.6 mm	5800 psi	4.6 in 115 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B4AE-04	1/4 in 6.4 mm	0.53 in 13.4 mm	5800 psi	2.8 in 70 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B4AE-05	5/16 in 7.9 mm	0.59 in 15 mm	5800 psi	3 in 76 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B4AE-06	3/8 in 9.5 mm	0.690 in 17.4 mm	5800 psi	3.6 in 90 mm	-40 to 300 °F -40 to 155 °C	Air Water
T8B4AE-08	1/2 in 12.7 mm	0.81 in 20.6 mm	5800 psi	4.6 in 115 mm	-40 to 300 °F -40 to 155 °C	Air Water