

Water Discharge Hose



High Pressure Water Discharge Hose**Application**

- Heavy duty water discharge hose where tougher operating conditions exist and high pressures are needed.

Cover

- Black abrasion and weather-resistant SBR rubber.

Reinforcement

- High tensile textile cords.

Tube

- Black SBR/NBR blend.

Item #	Nominal I.D.	Nominal O.D.	Max. Rec. Working Pressure	Temperature Range
T155AA150	1 1/2 in 38 mm	1.97 in 50 mm	300 psi	-22 to 176 °F
T155AA200	2 in 51 mm	2.56 in 65 mm	300 psi	-22 to 176 °F
T155AA250	2 1/2 in 63 mm	3.11 in 79 mm	300 psi	-22 to 176 °F
T155AA300	3 in 76 mm	3.62 in 92 mm	300 psi	-22 to 176 °F
T155AA400	4 in 102 mm	4.65 in 118 mm	300 psi	-22 to 176 °F
T155AA600	6 in 152 mm	6.69 in 170.0 mm	225 psi	-22 to 176 °F

SBR 150 PSI Layflat Water Discharge Hose**Application**

- High pressure, 150 PSI lay flat type hose for general industrial construction and irrigation.

Cover

- Black weather and ozone-resistant SBR rubber.

Reinforcement

- High tensile textile cords.

Tube

- Black EPDM rubber.

Branding

- ALFAGOMMA - ITALY - T253 10 BAR (150 PSI) WATER DISCHARGE (in green letters)

Item #	Item Name	Nominal I.D.	Nominal O.D.	Max. Rec. Working Pressure	Temperature Range
T253AA150	Layflat Water Discharge Hose	1 1/2 in 38 mm	1.81 in 46 mm	150 psi	-22 to 176 °F
T253AA200	Layflat Water Discharge Hose	2 in 51 mm	2.32 in 59 mm	150 psi	-22 to 176 °F
T253AA250	Layflat Water Discharge Hose	2 1/2 in 63 mm	2.80 in 71 mm	150 psi	-22 to 176 °F
T253AA300	Layflat Water Discharge Hose	3 in 76 mm	3.31 in 84 mm	150 psi	-22 to 176 °F
T253AA400	Layflat Water Discharge Hose	4 in 102 mm	4.33 in 110 mm	150 psi	-22 to 176 °F
T253AA600	Layflat Water Discharge Hose	6 in 152 mm	6.38 in 162 mm	150 psi	-22 to 176 °F
T253AA662	Elephant Trunk Hose	6 5/8 in 168 mm	7.01 in 178 mm	150 psi	-22 to 176 °F
T253AA800	Layflat Water Discharge Hose	8 in 203 mm	8.46 in 215 mm	150 psi	-22 to 176 °F
T253AA1000	Layflat Water Discharge Hose	10 in 254.0 mm	10.63 in 270 mm	150 psi	-22 to 176 °F
T253AA1200	Layflat Water Discharge Hose	12 in 305 mm	12.56 in 319 mm	100 psi	-22 to 176 °F

SBR Water Discharge Hose**Application**

- Water discharge hose for construction and irrigation.

Cover

- Black abrasion and weather-resistant SBR rubber.

Reinforcement

- High tensile textile cords.

Tube

- Black SBR/NBR blend.

Item #	Nominal I.D.	Nominal O.D.	Max. Rec. Working Pressure	Temperature Range
T254AA150	1 1/2 in 38 mm	1.89 in 48 mm	150 psi 10 bar	-22 to 176 °F
T254AA200	2 in 51 mm	2.40 in 61.0 mm	150 psi 10 bar	-22 to 176 °F
T254AA300	3 in 76 mm	3.46 in 88 mm	150 psi 10 bar	-22 to 176 °F
T254AA400	4 in 102 mm	4.49 in 114.0 mm	150 psi 10 bar	-22 to 176 °F
T254AA600	6 in 152 mm	6.54 in 166 mm	150 psi 10 bar	-22 to 176 °F
T254AA800	8 in 203 mm	8.62 in 219 mm	150 psi 10 bar	-22 to 176 °F



OH: 800-344-0150
GA: 888-492-2140

FAX: 937-454-2086
FAX: 770-428-0717