

300 PSI BLACK FUEL & OIL SUCTION & DELIVERY HOSE

Applications

Fuel and oil suction and discharge for up to 50% aromatic content. Designed for heavy duty applications. Note: Not recommended for use on a reel.

Construction

Cover: Black conductive CR - abrasion, ozone and hydrocarbon resistant.

Reinforcement:

High tensile textile cords, steel helix wires and static wire.

Tube:

Black conductive NBR.

Operating Conditions

Temperature Range: -22°F (-30°C) to 176°F (+80°C)

Branding

ALFAGOMMA - ITALY T620 - 20 BAR (300 PSI) PETROLEUM - S & D (in red letters) Ω.

Coupling Suggestions

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples.

Please note:

Proper grounding of static wire will prolong tube life.

ITEM:	ID:	OD:	WORKING PRESSURE	MIN. BEND RADIUS	TEMPERATURE	WEIGHT/ FOOT
T620AA200	2 IN	2.480 IN	300 PSI	8 IN	-22 to 176 °F	1.10 LBS/FT
T620AA300	3 IN	3.540 IN	300 PSI	12 IN	-22 to 176 °F	1.77 LBS/FT
T620AA400	4 IN	4.570 IN	300 PSI	16 IN	-22 to 176 °F	2.41 LBS/FT
T620AA600	6 IN	6.690 IN	300 PSI	24 IN	-22 to 176 °F	5.16 LBS/FT

