

HOT TAR AND ASPHALT HOSE



Applications

Hot tar and asphalt delivery service

Construction

Cover: Black CR – abrasion, ozone, hydrocarbon and fire resistant

Reinforcement: High tensile steel wire braids

Tube: Black NBR – hot tar and asphalt resistant

Safety Factor: 10:1

ITEM:	ID:	OD:	TEMPERATURE	WEIGHT/ PACKAGE	MAX PRESSURE
T631AA075	¾ IN	1.260 IN	-22 to 356 °F	50.0 LBS	300 PSI
T631AA100	1 IN	1.500 IN	-22 to 356 °F	77.0 LBS	300 PSI

HERCULES® II

Hercules II... the latest addition to our high working pressure multipurpose hoses is a cost effective alternative to our very successful and popular Hercules® 500 Multipurpose Hose. Hercules II was value-engineered to offer customers superior performance in harsh work sites like factories, foundries, manufacturing plants, mines, quarries and numerous other industrial applications. Non-conductive and MSHA approved

with a Class A RMA rating, Hercules II has a 4-spiral yarn reinforcement. This construction provides 500 psi working pressure in sizes 1/4" through 1-1/2" and 400 psi working pressure in the 2" size; all with a 4:1 burst safety factor. Hercules II's yellow, XNBR cover provides exceptional resistance to abrasion, oils and other petroleum based products. Hercules II is the best value and a great selection for any OEM or MRO application requiring long

life and exceptional performance in material transfer situations.

Cover Color: Yellow

Oil Resistance: High

Construction

Tube: NBR, RMA Class A

Cover: XNBR, RMA Class A

Reinforcement: 4-spiral yarn

Temperature Range: -40°F to +212°F

-40°C to +100°C

Packaging: Reels

ITEM:	ID:	OD:	WORKING PRESSURE	MIN. BEND RADIUS	WEIGHT/ FOOT
45454168662	¼ IN	.63 IN	500 PSI	1.50 IN	.14 LBS/FT
45454248662	3/8 IN	.75 IN	500 PSI	2.25 IN	.21 LBS/FT
45454328662	½ IN	.91 IN	500 PSI	3.00 IN	.24 LBS/FT
45454488662	¾ IN	1.19 IN	500 PSI	4.50 IN	.36 LBS/FT
45454648662	1 IN	1.50 IN	500 PSI	7.00 IN	.51 LBS/FT
00454520500	1.1/4 IN	1.75 IN	500 PSI	8.75 IN	.66 LBS/FT
00454524500	1.1/2 IN	2.09 IN	500 PSI	10.50 IN	.70 LBS/FT
00454532500	2 IN	2.64 IN	400 PSI	16 IN	1.45 LBS/FT



U.S. HOSE
& COUPLING

U.S. HOSE
& COUPLING