

FIRE HOSE: DOUBLE-JACKET

Quality

The fire hose assembly supplied under this specification shall be constructed with superior quality materials. NFPA 1961 standards shall be observed in production of the assembly, in order to ensure its quality and durability. Hose furnished under these specifications will have a potential service life warranty of one year; barring mistreatment that would render it unfit for service. Upon delivery, the hose shall be free from defects in materials and workmanship. Any defective hose will be replaced at no charge.

Jacket Construction

The single and double jackets will be woven evenly and be free of defects, including knots lumps or unsightly disfigurements that could jeopardize the integrity of the hose assembly. The warp yarn shall consist of staple polyester yarn. The use of filament or entangled yarn is expressly forbidden due to the lack of inherent abrasion resistance. The filler yarns shall be constructed of high strength, low elongation, filament polyester to reduce weight and increase flexibility.



ITEM:	SIZE	SERVICE TEST	PROOF TEST	BURST TEST	BOWL SIZE	WEIGHT/ FOOT
DP15-800-ECO	1.5 IN	400 PSI	800 PSI	1200 PSI	1 15/16 IN	.23 LBS/FT
DP25-800-ECO	2.5 IN	400 PSI	800 PSI	1200 PSI	3 IN	.42 LBS/FT

FIRE HOSE: RUBBER COVERED



Advantages

- Nitrile/PVC through-the-weave rubber covered construction
- UL Listed
- NFPA compliant attack hose
- Lightweight
- Heat resistant
- Chemical resistant
- Maintenance free
- Raised thick rib construction to aid abrasion resistance
- Diameters: 1", 2.5"

ITEM:	SIZE	SERVICE TEST	PROOF TEST	BURST TEST	BOWL SIZE	WEIGHT/ FOOT
RC15-600	1.5 IN	300 PSI	600 PSI	900 PSI	1 13/16 IN	.24 LBS/FT
RC25-600	2.5 IN	300 PSI	600 PSI	900 PSI	2 13/16 IN	.48 LBS/FT

U.S. HOSE & COUPLING

U.S. HOSE & COUPLING